

# Kanaflex<sup>®</sup>

## 101-PS

Corrugated exterior for superior flexibility.

*Weatherproof* . . . highly resistant to ozone, salt water and ultraviolet light.

*Pliable* . . . fits over pipe ends for flexible installations where ground or structure is subject to possible movement.

Smooth bore for unrestricted flow.

*Functional* . . . can be "welded" to rigid PVC pipe using conventional PVC cements.

*Secure* . . . provides a superior hold to rigid pipe when used with Kanaflex pipe-size "Power Lock" clamps. (see illustration)

Available in lengths of 100 ft. for rapid installation and lower labor costs.

POWERLOCK CLAMP PS  
(PIPE SIZE)



### SPECIFICATIONS

SIZE	OUTSIDE DIAMETER Inches	PITCH Inches	MIN. BENDING RADIUS 72°F, Inches	WORKING PRESSURE 72°F, P.S.I.	BURSTING PRESSURE 72°F, P.S.I.	VACUUM RATING 72°F, In. / Hg.	WEIGHT Lbs. / Ft.
2.375"	2.76	0.41	2.6	35	115	29.8	0.68
3.5"	4.00	0.63	3.5	30	100	29.8	1.20
4.5"	5.79	0.67	6.5	30	100	28.0	1.70

**Kanaflex<sup>®</sup>**  
CORPORATION

800 Woodlands Parkway  
Vernon Hills, IL 60061

DISTRIBUTED BY:

**GOODYEAR**  
RUBBER PRODUCTS INC.

Call Toll Free: **1-866-711-4673**

WebSales@GoodyearRubberProducts.com

**We Ship  
World Wide**