

IMPRESSION TOP / SLITTABLE CHEVRON BELT

#242 PVC 150 Black Chevron Top II x Brushed Bottom

The chevron pattern of alternating rows form a unique pattern to effectively convey free flowing bulk solids. A very popular specification for heavy duty applications in the transportation of grains and fertilizers up steep inclines.

Temperature range: 20° F to 180° F. **Thickness:** 1/4". **Weight:** .110 piw.

Minimum pulley diameter: 3". **Recommended fasteners:** #2 Hook, #125 Staple, #20 Alligator.

Part Number: 20034605



#204 PVC 150 Black Crescent Top x Brushed Bottom

Half moon shaped profiles effectively move bulk materials up steep inclines. This is the specification of choice for fertilizers, grain, and feed conveying. Durable crescents overlap to assure a smooth quiet return on conveyor rollers. By running the belt in opposite direction, the crescent shapes can assist in draining liquids from wet products.

Temperature range: 20° F to 180° F. **Thickness:** 1/4". **Weight:** .110 piw.

Minimum pulley diameter: 3". **Recommended fasteners:** #2 Hook, #125 Staple, #20 Alligator.

Part Number: 20035527



#99 3 Ply Polyester 105 White Tyler Wire x Friction Surface

This specification features an impression capable of high traction on moderate inclines. Often used in bakeries, produce applications, and for handling packages and small parts. It is non-marking, oil and grease resistant. Meets FDA, is USDA accepted.

Temperature range: 0° F to 250° F. **Thickness:** 1/8". **Weight:** .060 piw.

Minimum pulley diameter: 2 1/2". **Recommended fasteners:** #1 Hook, #125 Staple, #7 Alligator.

Part Number: 20028700



#102 3 Ply Polyester 135 White Nitrile Meat Cleat x Friction Surface

This belt specification is an excellent choice for moving meat and poultry products during processing at federally inspected plants. Smooth surfaces are easily cleaned. Inverted v-shaped profiles are 1/8" high and spaced evenly on 1" centers. Meets FDA requirements, is USDA accepted.

Temperature range: 0° F to 250° F. **Thickness:** 9/64". **Weight:** .085 piw.

Minimum pulley diameter: 3 1/2". **Recommended fasteners:** #2 SP Hook, #125 Staple, #15 Alligator.

Part Number: 20028506



#233 2 Ply Polyester Inverted Pyramid PVC Top Cover x Bare Back

This belt is excellent for handling food and bakery products (bread dough) or in the rubber industry for the transport of unvulcanized rubber. Odorless and taste free with good resistance to fats and oils. Meets FDA requirements, is USDA accepted.

Temperature range: 20° F to 180° F. **Thickness:** 3/32". **Weight:** .047 piw.

Minimum pulley diameter: 1 1/2". **Recommended splice:** 25 LP Hook, #62 Staple, #1 Alligator.

Part Number: 24005980



SLITTABLE CHEVRON BELT

#57A 2 Ply 220 1/8 x 1/16 Durocleat Grade 2

Flexible synthetic fabric has two high strength plies. Top cover profiles are 1/4" high and 3/8" wide, cross section molded as part of the cover during manufacturing. The resulting profile is v-shaped, approximately 6" wide and staggered in rows across full width of the top cover. Excellent choice for elevating bulk materials such as surface grindings from road machinery. Commonly used as a belt replacement on asphalt scalpers, rotomills or road planers.

Temperature range: -25° F to 225° F. **Thickness:** 5/16" plus 1/4" x 3/8" profile. **Weight:** .210 piw. **Minimum pulley diameter:** 12". **Recommended fasteners:** #190 Solid Plate, #375 Bolt On, #R5 Rivet.

Part Number: 20029603

