

#60A 2 Ply 100 Black RMV x Friction Surface

Excellent all-purpose conveyor belt with a smooth 1/16" RMV top cover. Used regularly on assembly and packaging lines, and other applications requiring resistance to some oils associated with products being moved. Carcass is flexible, yet strong for stretch resistance. Cover resists oil, grease, and animal fats.

Temperature range: 20° F to 180° F. **Thickness:** 7/64". **Weight:** .070 piw.
Minimum pulley diameter: 1 1/2". **Recommended fasteners:** #1SP Hook; #62 Staple; #7 Alligator.

Part Number: 20032940



#60B 3 Ply 150 Black RMV x Friction Surface

Excellent multiple purpose light duty conveyor belt. Smooth 1/16". Used regularly on assembly and packaging lines, and other applications requiring resistance to some oils associated with products being moved. Carcass is flexible, yet strong. Cover resists oil, grease, and animal fats.

Temperature range: 20° F to 180° F. **Thickness:** 1/8". **Weight:** .080 piw.
Minimum pulley diameter: 3". **Recommended fasteners:** #1SP Hook, #62 Staple, #7 Alligator.

Part Number: 20032945



#61A PVC 120 Black Roughtop x Friction Surface

This medium duty textured roughtop PVC belt has a nonskid surface that enables packages, boxes, cases, and other products to be conveyed on both inclines and declines. Solid woven uni-ply construction and PVC compounds combine properties for high traction and performance, even with light oil, grease, water, and industrial chemicals present. Synthetic carcass has high strength and low stretch characteristics.

Temperature range: 20° F to 180° F. **Thickness:** 11/64". **Weight:** .100 piw.
Minimum pulley diameter: 2 1/2". **Recommended fasteners:** #1 Hook, #125 Staple, #15 Alligator.

Part Number: 20035506



#62A PVC 100 Black Bucket Top Oil Resistant x Friction Surface

This PVC profile top belt features a multitude of "bucket" projections to aggressively assist the belt in elevating bulk solids. In very wet applications, the belt can run in the opposite direction to assist in draining off fluids.

Temperature range: 20° F to 180° F. **Thickness:** 15/64". **Weight:** .085 piw.
Minimum pulley diameter: 2". **Recommended fasteners:** #1 SP Hook, #125 Staple, #7 Alligator.

Part Number: 20033600



#62B PVC 120 Black Crescent Top x Friction Surface

Crescent top profiles project from the belt surface to aggressively assist the belt in moving bulk solids. By running the belt in opposite direction, the crescent shapes can assist in draining liquids from wet products. Crescents overlap to assure a smooth quiet running on return rolls.

Temperature range: 20° F to 180° F. **Thickness:** 15/64". **Weight:** .085 piw.
Minimum pulley diameter: 2". **Recommended fasteners:** #1 SP Hook, #62 Staple, #7 Alligator.

Part Number: 20035525



#55A PVC 120 Black Chevron Top II Oil Resistant x Friction Surface

The herringbone pattern of alternating rows of solid PVC chevron profiles form a cover highly capable of moving free flowing bulk solids. Materials such as grains, food stuffs, feeds and fertilizers can be carried up steep inclines.

Temperature range: 20° F to 180° F. **Thickness:** 1/4". **Weight:** .088 piw.
Minimum pulley diameter: 2 1/2". **Recommended fasteners:** #1 Hook, #125 Staple, #7 Alligator.

Part Number: 20034603

