



CUSTOM FABRICATION


HOT VULCANIZED




Roofing Cleat



Drilled and Siped




Special Cleats




Heavy Duty Beefy Cleat

Height
5/8"
1"
1 1/2"
2"
3"
4"
5"
6"




Standard T-Cleat

Height
3/4"
1"
1 1/2"
2"
2 1/2"
3"




Vanner Edge

Height
1/2"
3/4"
1"
1 1/2"
2"
2 1/2"
3"



Square Cleat


Height
3/8" x 3/8"
1/2" x 1/2"
3/4" x 3/4"
1" x 1"



Scoop Cleat

Cold vulcanized


Height
3"
3 1/2"
4"
4 1/2"




V-Guides

Size
A
O
B
C
D
E


COMMON NOTCHING OPTIONS




REGULAR
not notched



NOTCHED



INDENTED



CUT-OUT

APPLICATIONS:

Apache's know-how brings you cleats, vanner edges, and v-guides in a variety of designs, each of which is engineered for the maximum performance of the material being conveyed. All are hot vulcanized to the base belt.

- STAGGERED, SPACED OR NOTCHED, APACHE'S UNIQUE VULCANIZING METHODS ASSURE YOU OF A PROFESSIONALLY FABRICATED BELT.
- FABRICATION IS AVAILABLE ON NUMEROUS INDUSTRIAL AND FOOD GRADE BELTS.
- BLACK COMPOUNDS AVAILABLE ARE: STANDARD BLACK, MSHA, OIL, AND HEAT RESISTANT.
- WHITE COMPOUNDS ARE OIL AND FAT RESISTANT (FDA/USDA).
- CORRUGATED SIDEWALL IS FABRICATED ON STANDARD OR CROSS-RIGID CONSTRUCTED BELTING.