

Quick,

Easy Assembly

Flange Ball Valves/Fittings

- Quick and easy assembly. No pipe tape or sealant necessary.
- Positive seals.
- Easy on/off hose connections.
- 360° orientation.
- Valves and fittings are manufacture from glass reinforced polypropylene for strength and durability. Will not rust or corrode.



Valves

- Self-aligning ball rotates freely against Teflon® seats.
- Unique body-to-flange design allows for low torque on/off operations.
- Viton O-ring stem seal and EPDM O-ring body seal.
- Pressure rated at 125 psi @ 70°F
- All valves tested by air pressure under water.



DESCRIPTION	PART NO.	LIST PRICE
1" Full Port Flange x Flange	63028	30.80
2" Full Port Compact Flange x Flange	63123	48.35
3" Full Port Flange x Flange	63125	128.20

Recommended operating pressure
100 psi @ 0°F • 125 psi @ 70°F • 70 psi @ 150°F

Stainless Steel Worm Screw Hose Clamps for Flange Fittings



DESCRIPTION	PART NO.	LIST PRICE
1"	62932	6.08
2"	62933	7.56
3"	62934	10.58

EPDM Flange Gasket for Flange Fittings



DESCRIPTION	PART NO.	LIST PRICE
1"	62935	.88
2"	61574	.98
3"	61575	1.02

