BELTWALL CORRUGATED SIDEWALL BELTING

BELTWALL®

Beltwall is one of the world's leading producers of cross-rigid corrugated sidewall belting. In the Western Hemisphere and Asia, Beltwall has an outstanding record of successful bulk handling installations.

Three factors contribute to Beltwall's superior performance on high-lift systems:

- 1. Beltwall's unique combination of fiberglass cross-rigid plies and special high-strength rubber create the most cross-rigid base belt available.
- 2. Beltwall's sidewall construction of fiber-loaded compounds keeps incidental cuts or tears from propagating.
- 3. Beltwall's urethane cleats bolted into cleat bases that are vulcanized to the base belt are more durable than rubber cleats of similar size. All Beltwall cleats are hot-vulcanized onto the base belt to ensure the highest adhesion levels possible.


Beltwall offers the widest variety of corrugated sidewalls in the industry – from 1" through 16" – with metric sizes readily available. Sizes above 5" are reinforced with a specially woven fabric ply to provide exceptional strength and performance.

BASIC CONFIGURATIONS

Beltwall belts carry material in any plane from horizontal to vertical. The most common conveyor shapes include straight incline, "L," and "S" shapes (see page 34) but almost any configuration is possible.

CONSTRUCTIONS

Each Beltwall belt consists of two corrugated sidewalls bonded to a cross-rigid base belt. The walls can be recessed for clearance and belt support through bend sections. Beltwall offers three distinct cleat profiles (see table on page 33) to provide optimal capacity at any angle. White food grade Beltwall belts are available with sidewalls from 1" to 5". These belts are acceptable for most applications governed by FDA regulations.







All Beltwall products are packaged to ensure they arrive in "factory new" condition, whether shipped across the state, country, or world.

RUBBER COMPOUNDS AVAILABLE

Black Standard
Black Moderately Oil Resistant
Black High Heat Resistant

Black High Oil Resistant

Black Flame Retardant (MSHA Approved)

White Oil and Fat Resistant (FDA)

Call Toll Free: 1-866-711-4673

We Ship World Wide