


DIN Metric Fittings

Reducing Adjustable Coupling VS8014 Series



PRODUCT ID	DESCRIPTION	D1	D2	L1	S1	S2	S3	Standard Material From Stock				
								S	FG	SS	B	
VS8014-L08-L06	Reducing Adjustable Coupling	6	8	40.5	12	17	14	•				
VS8014-L10-L06	Reducing Adjustable Coupling	6	10	41.5	12	19	14	•				
VS8014-L10-L08	Reducing Adjustable Coupling	8	10	42.5	14	19	17	•				
VS8014-L12-10	Reducing Adjustable Coupling	10	12	45.5	17	22	19	•				
VS8014-L12-L06	Reducing Adjustable Coupling	6	12	44.5	14	22	14	•				
VS8014-L12-L08	Reducing Adjustable Coupling	8	12	44.5	14	22	17	•				
VS8014-L15-L06	Reducing Adjustable Coupling	6	15	46	17	27	14	•				
VS8014-L15-L08	Reducing Adjustable Coupling	8	15	46	17	27	17	•				
VS8014-L15-L10	Reducing Adjustable Coupling	10	15	47	17	27	19	•				
VS8014-L15-L12	Reducing Adjustable Coupling	12	15	48	19	27	22	•				
VS8014-L18-L06	Reducing Adjustable Coupling	6	18	45.5	19	32	14	•				
VS8014-L18-L08	Reducing Adjustable Coupling	8	18	45.5	19	32	17	•				
VS8014-L18-L10	Reducing Adjustable Coupling	10	18	46.5	19	32	19	•				
VS8014-L18-L12	Reducing Adjustable Coupling	12	18	46.5	19	32	22	•				
VS8014-L18-L15	Reducing Adjustable Coupling	15	18	47.5	24	32	27	•				
VS8014-L22-L10	Reducing Adjustable Coupling	10	22	47.5	24	36	19	•				
VS8014-L22-L12	Reducing Adjustable Coupling	12	22	47.5	24	36	22	•				
VS8014-L22-L18	Reducing Adjustable Coupling	18	22	50.5	27	36	32	•				
VS8014-L28-L12	Reducing Adjustable Coupling	12	28	49	30	41	22	•				
VS8014-L28-L15	Reducing Adjustable Coupling	15	28	50	30	41	27	•				
VS8014-L28-L18	Reducing Adjustable Coupling	18	28	52	30	41	32	•				
VS8014-L28-L22	Reducing Adjustable Coupling	22	28	54	32	41	36	•				
VS8014-L35-L15	Reducing Adjustable Coupling	15	35	56.5	36	50	27	•				
VS8014-L35-L18	Reducing Adjustable Coupling	18	35	58.5	36	50	32	•				
VS8014-L35-L22	Reducing Adjustable Coupling	22	35	60.5	36	50	36	•				
VS8014-L35-L28	Reducing Adjustable Coupling	28	35	61.5	41	50	41	•				
VS8014-L42-L15	Reducing Adjustable Coupling	15	42	60	46	60	27	•				
VS8014-L42-L18	Reducing Adjustable Coupling	18	42	61	46	60	32	•				
VS8014-L42-L22	Reducing Adjustable Coupling	22	42	63	46	60	36	•				
VS8014-L42-L28	Reducing Adjustable Coupling	28	42	64	46	60	41	•				
VS8014-L42-L35	Reducing Adjustable Coupling	35	42	69	46	60	50	•				
VS8014-LSS-L15	Reducing Adjustable Coupling	15	22	48.5	24	36	27	•				
VS8014-S08-S06	Reducing Adjustable Coupling	6	8	45	14	19	17	•				
VS8014-S10-S06	Reducing Adjustable Coupling	6	10	47	14	22	17	•				
VS8014-S10-S08	Reducing Adjustable Coupling	8	10	49	17	22	19	•				
VS8014-S12-S06	Reducing Adjustable Coupling	6	12	47	14	24	17	•				
VS8014-S12-S08	Reducing Adjustable Coupling	8	12	49	17	24	19	•				
VS8014-S12-S10	Reducing Adjustable Coupling	10	12	50	19	24	22	•				
VS8014-S14-S06	Reducing Adjustable Coupling	6	14	50	17	27	17	•				
VS8014-S14-S08	Reducing Adjustable Coupling	8	14	52	17	27	19	•				
VS8014-S14-S10	Reducing Adjustable Coupling	10	14	53	19	27	22	•				
VS8014-S14-S12	Reducing Adjustable Coupling	12	14	55	22	27	24	•				
VS8014-S16-S06	Reducing Adjustable Coupling	6	16	50	17	30	17	•				
VS8014-S16-S08	Reducing Adjustable Coupling	8	16	52	17	30	19	•				
VS8014-S16-S10	Reducing Adjustable Coupling	10	16	53	19	30	22	•				
VS8014-S16-S12	Reducing Adjustable Coupling	12	16	55	22	30	24	•				
VS8014-S16-S14	Reducing Adjustable Coupling	14	16	58	24	30	27	•				
VS8014-S20-S08	Reducing Adjustable Coupling	8	20	56	22	36	19	•				
VS8014-S20-S10	Reducing Adjustable Coupling	10	20	57	22	36	22	•				
VS8014-S20-S12	Reducing Adjustable Coupling	12	20	59	22	36	24	•				
VS8014-S20-S14	Reducing Adjustable Coupling	14	20	62	24	36	27	•				
VS8014-S20-S16	Reducing Adjustable Coupling	16	20	62	27	36	30	•				
VS8014-S25-S10	Reducing Adjustable Coupling	10	25	60	27	46	22	•				
VS8014-S25-S12	Reducing Adjustable Coupling	12	25	62	27	46	24	•				
VS8014-S25-S14	Reducing Adjustable Coupling	14	25	65	27	46	27	•				
VS8014-S25-S16	Reducing Adjustable Coupling	16	25	65	32	46	30	•				
VS8014-S25-S20	Reducing Adjustable Coupling	20	25	70	32	46	36	•				
VS8014-S30-S12	Reducing Adjustable Coupling	12	30	65	32	50	24	•				
VS8014-S30-S14	Reducing Adjustable Coupling	14	30	68	32	50	27	•				
VS8014-S30-S16	Reducing Adjustable Coupling	16	30	68	32	50	30	•				
VS8014-S30-S20	Reducing Adjustable Coupling	20	30	73	32	50	36	•				
VS8014-S30-S25	Reducing Adjustable Coupling	25	30	78	41	50	46	•				
VS8014-S38-S16	Reducing Adjustable Coupling	16	38	74	41	60	30	•				
VS8014-S38-S20	Reducing Adjustable Coupling	20	38	79	41	60	36	•				
VS8014-S38-S25	Reducing Adjustable Coupling	25	38	84	41	60	46	•				