


Reducing Union N2403


INCH OD Tubes



Part No.	T Tube OD	Tx Tube OD	A	C	Cx	D	Dx	E min.	F A/F	G A/F	Gx A/F	H
N2403-04-02	1/4	1/8	38.6	17.8	15.3	15.3	12.7	2.4	14	14	11	24.6
N2403-05-02	5/16	1/8	39.6	18.6	15.3	16.3	12.7	2.4	14	16	11	25.7
N2403-05-04	5/16	1/4	42.2	18.6	17.8	16.3	15.3	4.8	14	16	14	27.5
N2403-06-02	3/8	1/8	40.9	19.3	15.3	16.8	12.7	2.4	16	17	11	26.9
N2403-06-04	3/8	1/4	43.2	19.3	17.8	16.8	15.3	4.8	16	17	14	28.5
N2403-08-02	1/2	1/8	45.2	21.8	15.3	22.9	12.7	2.4	22	22	11	28.5
N2403-08-04	1/2	1/4	47.0	21.8	17.8	22.9	15.3	4.8	22	22	14	29.5
N2403-08-06	1/2	3/8	48.5	21.8	19.3	22.9	16.8	7.1	22	22	17	31.0
N2403-10-06	5/8	3/8	49.3	21.8	19.3	24.4	16.8	7.1	24	25	17	31.8
N2403-10-08	5/8	1/2	52.0	21.8	21.8	24.4	22.9	10.4	24	25	22	31.8
N2403-12-04	3/4	1/4	49.3	21.8	17.8	24.4	15.3	4.8	27	28.5	14	31.8
N2403-12-06	3/4	3/8	50.8	21.8	19.3	24.4	16.8	7.1	27	28.5	17	33.3
N2403-12-08	3/4	1/2	53.6	21.8	21.8	24.4	22.9	10.4	27	28.5	22	33.3
N2403-16-08	1	1/2	60.5	26.5	21.8	31.2	22.9	10.4	35	38	22	38.1
N2403-16-12	1	3/4	60.5	26.5	21.8	31.2	24.4	15.8	35	38	28.5	38.1
N2403-20-16	1-1/4	1	92.2	38.9	26.4	41.2	31.2	22.3	45	50	38	48.0
N2403-24-20	1-1/2	1-1/4	60.5	26.5	21.8	31.2	24.4	15.8	55	57	50	53.6

Male Connector N2404

INCH OD Tubes x Male NPT Threads



Part No.	T Tube OD	P NPT Male	A	B	C	D	E min.	F A/F	G A/F	H
N2404-01-01	1/16	1/16	23.9	9.6	11.0	8.6	1.3	8	8	20.0
N2404-01-02	1/16	1/8	26.2	9.6	11.0	8.6	1.3	14	8	22.4
N2404-02-02	1/8	1/8	30.5	9.6	15.3	12.7	2.4	11	11	23.9
N2404-02-04	1/8	1/4	35.6	14.3	15.3	12.7	2.4	14	11	29.0
N2404-04-02	1/4	1/8	32.8	9.6	17.8	15.3	4.8	14	14	25.4
N2404-04-04	1/4	1/4	37.8	14.3	17.8	15.3	4.8	14	14	30.5
N2404-04-06	1/4	3/8	38.4	14.3	17.8	15.3	4.8	19	14	31.0
N2404-04-08	1/4	1/2	44.7	19.1	17.8	15.3	4.8	22	14	37.4
N2404-05-04	5/16	1/4	38.6	14.3	18.5	16.3	6.3	14	16	31.2
N2404-06-02	3/8	1/8	35.3	9.6	19.3	16.8	4.8	16	17	27.9
N2404-06-04	3/8	1/4	39.8	14.3	19.3	16.8	7.1	16	17	32.5
N2404-06-06	3/8	3/8	39.8	14.3	19.3	16.8	7.1	19	17	32.5
N2404-06-08	3/8	1/2	41.2	19.1	19.3	16.8	7.1	22	17	38.9
N2404-08-04	1/2	1/4	43.4	14.3	21.8	22.9	7.1	22	22	33.3
N2404-08-06	1/2	3/8	43.4	14.3	21.8	22.9	9.6	22	22	33.3
N2404-08-08	1/2	1/2	49.0	19.1	21.8	22.9	10.4	22	22	38.9
N2404-08-12	1/2	3/4	50.5	19.1	21.8	22.9	10.4	27	22	40.4
N2404-08-16	1/2	1	57.1	23.8	21.8	22.9	10.4	35	22	47.0
N2404-10-06	5/8	3/8	44.2	14.3	21.8	24.4	9.6	24	25	34.0
N2404-10-08	5/8	1/2	49.0	19.1	21.8	24.4	10.4	24	25	38.9
N2404-12-08	3/4	1/2	50.5	19.1	21.8	24.4	10.4	27	28.5	40.4
N2404-12-12	3/4	3/4	50.5	19.1	21.8	24.4	15.8	27	28.5	40.4
N2404-12-16	3/4	1	57.1	23.8	21.8	24.4	15.8	35	28.5	47.0
N2404-14-12	7/8	3/4	50.5	19.1	21.8	26.0	15.8	30	32	40.4
N2404-16-08	1	1/2	57.4	19.1	26.4	31.2	10.4	35	38	45.2
N2404-16-12	1	3/4	57.4	19.1	26.4	31.2	15.8	35	38	45.2
N2404-16-16	1	1	62.2	23.8	26.4	31.2	22.3	35	38	50.0
N2404-20-16	1-1/4	1	77.2	23.8	38.9	41.2	22.3	46	50	55.2
N2404-20-20	1-1/4	1-1/4	77.2	23.8	38.9	41.2	27.6	46	50	55.2
N2404-24-24	1-1/2	1-1/2	88.9	26.2	45.2	50.0	34.0	55	57	61.7
N2404-32-32	2	2	113.5	26.9	62.7	67.6	46.0	70	76	76.2

Bored-Through Connectors available in all of these sizes. Add suffix "BT" to the above part numbers to designate bored-through male connector.