



Gauge Adaptor DGA

G Thread	h mm/in	SW mm/in	Brennan Order No.	Description
1/4 NPT	54 / 2.12	19 / .75	DGA2404-04	DGA – FNPT
1/4 BSPP	54 / 2.12	19 / .75	DGA7002-04	DGA – FBSPP
1/2 BSPP	64 / 2.52	27 / 1.06	DGA7002-08	DGA – FBSPP



Direct Gauge Adaptor DDG

G Thread	h mm/in	SW mm/in	Brennan Order No.	Description
1/4 NPT	41 / 1.61	19 / .75	DDGA2404-04	DDG – FNPT
1/4 BSPP	41 / 1.61	19 / .75	DDGA7002-04	DDG – FBSPP
1/2 BSPP	51 / 2.0	27 / 1.06	DDGA7002-08	DDG – FBSPP



Pressure Gauges

Standard Stock Pressure Ranges

Brennan Order No.	St. Steel 63 Series Stem	St. Steel 63 Series Panel	St. Steel 100 Series Stem	St. Steel 100 Series Panel	Forged Bronze 63 Series Stem
DG-15-30	•	•	•	•	•
DG-600	•	•	•	•	•
DG-1000	•	•	•	•	•
DG-7500	•	•	•	•	•

Specifications

- Glycerine Filled for Accuracy
- Copper Alloy Bourden Tube
- Dual Scales
- Built-in Relief Valve
- Operating Temperatures
Ambient: -4°F to 140°F (-20°C to 60°C)
Media: 140°F (+60°C)
- Acrylic Lens
- Accuracy + 1.5% of Full Scale
- Built-in Snubber



Series	Style	Size	A	B	C	D	E	F	G	
Stainless Steel	Stem Mount	2-1/2"	in 63	2.5 63	2.1 53	1.2 31	0.51 13	0.26 6.5	– –	– –
	Panel Mount U-Bolt	2-1/2"	in 63	2.5 63	2.8 72	2.4 62	1.2 31	0.26 6.5	– –	– –
	Panel Mount Front Flange	2-1/2"	in 85	3.3 85	2.9 75	2.5 63	2.44 62	1.2 31	0.08 2	0.08 2
	Stem Mount	4"	in 107	4.2 107	3.4 86	1.85 47	0.3 7.5	0.64 16.3	– –	– –
	Panel Mount U-Bolt	4"	in 107	4.2 107	4.25 108	3.15 80	1.85 47	0.3 7.5	– –	– –
	Panel Mount Front Flange	2-1/2"	in 132	5.2 132	4.7 118	4.2 107	3.15 80	1.85 47	0.05 1.25	0.3 7.5
Forged Bronze	Stem Mount	2-1/2"	in 63.5	2.5 63.5	2.13 54	1.5 38	0.44 11	0.50 12.2	– –	– –