

HH-P-31 F TY1, CL1

- 60" Wide X 50 Yds Per Roll
- Thickness: .041"
- Weight: 24 oz/sq. yd
- Service Temperature: 1000°F
- Stainless Steel Wire Inserted Fiberglass Fabric meets HHP-P-31F TY1, CL1. Certifications available upon request.
- Test reports to specifications available at cost upon request.

ASK YOUR CUSTOMER SERVICE REP. ABOUT THE VARIETY OF CUSTOM-MADE MANUFACTURED PRODUCTS FROM THIS PRODUCT.

TETRAGLAS® NEEDED BLANKET

Tetraglas® Needed Blanket is manufactured from 100% non-woven E-type fiberglass textile fibers. It is used in a variety of applications and specifically designed for use in aerospace, automotive, construction and industrial applications. Specific applications include: removable pads, furnace and oven insulation, pipe insulation, power generating equipment plus many more.

- Odorless
- Fire-resistant
- Service temperature: 1000°F

*Sold in Full Roll Quantities Only.

THICKNESS	1/4"	1/2"	3/4"	1"
DENSITY	9#	9#	9#	9#
WIDTH	60"	60"	60"	60"
ROLL LENGTH	150 FT.	75 FT.	45 FT.	45 FT.
SQ. FT/ ROLL	750	375	225	225