

Tadpole Tape

WIRE INSERTED TETRAGLAS-T® TADPOLE TAPE W/FIBERGLASS ROPE CORE

For operating temperatures to 550°F (290°C) against steam, water, air and gases.

Manufactured from Tetraglas® cloth with friction coating of natural or SBR rubber which is formed over core material of Tetraglas® rope providing a resilient, non-absorbent gasketing material for service against steam, air, water and gases to 550°F.

Available with other core materials, please call for pricing.

Manufactured in standard 25' or 50' lengths.

Standard Available Bulb Diameters: 3/8", 1/2", 5/8", 3/4", 1"

Standard Available O/A Widths: 1", 1-1/4", 1-1/2", 1-3/4", 2", 2-1/2", 3"

*Other sizes available to meet your needs.

TETRAGLAS® DRY-STITCHED TADPOLE TAPE W/FIBERGLASS ROPE CORE

For service conditions to 1000°F (538°C) continuous against air and gases.

Manufactured from plain cloth formed over core material of Tetraglas® rope and stitched to provide the characteristic tail structure. A soft, resilient gasketing material for effective sealing on light metal flanges and where limited bolting force is available and where doors and other closures rest on the bulb of the packing. Dry stitched Tetraglas® Tadpole Tapes maintain their efficiency throughout prolonged service in high temperature applications to 1000°F.

Manufactured in standard 50' or 100' lengths.

Std. Available Bulb Diameters: 3/8", 1/2", 5/8", 3/4", 1"

Std. Available O/A Widths: 1", 1-1/4", 1-1/2", 1-3/4", 2", 2-1/2", 3"

*Other sizes available to meet your needs.

TETRAGLAS® DRY-STITCHED TADPOLE TAPE – STAINLESS STEEL MESH CORE

Manufactured from plain Tetraglas® cloth formed over a core of inconel mesh and stitched to provide the characteristic tail structure. A soft, resilient gasketing material for effective sealing on light metal flanges and where limited bolting force is available and where doors and other closures rest on the bulb of the packing. For applications of 1000°F.

Manufactured in standard 50' or 100' lengths.

Std. Available Bulb Diameters: 3/8", 1/2", 5/8", 3/4", 1"

Std. Available O/A Widths: 1", 1-1/4", 1-1/2", 1-3/4", 2", 2-1/2", 3"

*Other sizes available to meet your needs.

****Ask your Customer Service Rep. about endless tadpole gaskets or a stainless steel mesh outside cover for any of your tadpole needs which require extra abrasion resistance.***