


# Compression Packings

Compression type packings are the oldest and still the most common means of controlling fluid loss in mechanical equipment. Made from relatively soft, pliant materials, they find major use in rotary, centrifugal and reciprocating pumps, valves, expansion joints, and many other types of mechanical equipment. Darco Southern, Inc. offers a general line of such packings.



---

## **NO. 1600 TWISTED NON-ASBESTOS VALVE STEM PACKING**

Manufactured of synthetic yarns, twisted lubricated and graphited. Will seal up to 500°F against hot and cold air, water, and ammonia.

- AVAILABLE IN ALL STANDARD SIZES
- 1/2 INCH LARGEST AVAILABLE
- AVAILABLE IN 25-100 LB REEL, 5 LB SPOOL, & 1 LB SPOOL

---

## **NO. 1620 SQUARE BRAIDED NON-ASBESTOS PUMP PACKING**

Manufactured of synthetic fiber and impregnated with lubricant and graphite, 500°F, pH range 4 - 10.

- AVAILABLE IN ALL STANDARD SIZES
- LARGER SIZES ARE AVAILABLE
- AVAILABLE IN 25-100 LB REEL, 5 LB SPOOL, & 1 LB SPOOL

---

## **NO. 1650 PTFE IMPREGNATED NON-ASBESTOS SQUARE BRAIDED PACKING**

Manufactured of synthetic fiber with each strand individually impregnated with PTFE plus break-in lubrication. 500°F.

- AVAILABLE IN ALL STANDARD SIZES
- LARGER SIZES ARE AVAILABLE
- AVAILABLE IN 25-100 LB REEL, 5 LB SPOOL, & 1 LB SPOOL

---

## **NO. 640 FLAX PACKING – REGULAR**

Recommended for use against cold water, brine and cold oil. Can be used on rods and plungers of pumps, rams or hydraulic presses, and stern tube glands. For temp. up to 200°F.

- AVAILABLE IN ALL STANDARD SIZES
- LARGER SIZES ARE AVAILABLE
- AVAILABLE IN 25-100 LB REEL, 5 LB SPOOL, & 1 LB SPOOL

---

## **NO. 660 TEFLON® FILAMENT PACKING**

Manufactured from pure Teflon® fibers in special braid construction which provides a packing having increased sealing contact at reduced gland pressures. The Teflon® suspensoid lubricant is controlled to assure compressibility and recovery factors.

- AVAILABLE IN ALL STANDARD SIZES
- LARGER SIZES ARE AVAILABLE
- AVAILABLE IN 25-100 LB REEL, 5 LB SPOOL, & 1 LB SPOOL