

Cam and Groove

Polypropylene Cam and Groove Adapters

SAFETY
ALERT

Polypropylene not recommended for use with Teflon® gaskets.

Type A Adapters



Male Adapter x
Female NPT

Size	Polypropylene Part #	Price/E	Pkg Qty
¾" x ½"	PPA50	\$4.75	24
¾"	PPA75	4.75	24
1"	PPA100	5.20	24
1½" x 1¼"	PPA125	5.40	24
1½"	PPA150	5.75	24
2"	PPA200	6.85	24
3"	PPA300	15.30	24
4"	PPA400	25.15	8

Type F Adapters



Male Adapter x
Male NPT

Size	Polypropylene Part #	Price/E	Pkg Qty
¾" x ½"	PPF50	\$5.25	24
¾"	PPF75	5.25	24
1"	PPF100	5.90	24
1½" x 1¼"	PPF125	6.00	24
1½"	PPF150	6.00	24
2"	PPF200	7.95	24
3"	PPF300	19.55	24
4"	PPF400	25.15	8

Type E Adapters



Male Adapter x
Hose Shank

Size	Polypropylene Part #	Price/E	Pkg Qty
¾" x ½"	PPE50	\$5.25	24
¾"	PPE75	5.25	24
1"	PPE100	5.90	24
1½" x 1¼"	PPE125	6.00	24
1½"	PPE150	6.00	24
2"	PPE200	7.95	24
3"	PPE300	19.55	24
4"	PPE400	25.15	8

Type P Dust Plugs ¹



Dust Plug ¹

Size	Polypropylene Part #	Price/E	Pkg Qty
¾"	PPP75	\$4.75	24
1"	PPP100	5.20	24
1½"	PPP150	5.70	24
2"	PPP200	7.70	24
3"	PPP300	15.30	24
4"	PPP400	20.00	8

- Recommended for a maximum working pressure of **125 PSI** (½" - 1"), **100 PSI** (1¼" - 2") and **75 PSI** (3" - 4"). Recommendations based on the use of mating Dixon fittings at an ambient temperature of **70°F** with standard seal installed.
- ½" couplers and adapters will interchange with ¾" couplers and adapters. Only the threads and barbs are ½".
- 1¼" couplers and adapters will interchange with 1½" couplers and adapters. Only the threads and barbs are 1¼".
- Polypropylene cam and groove should not be mixed with aluminum fittings. **SAFETY ALERT**
- Adapters are manufactured from a glass-filled polypropylene.

¹ Dust caps and dust plugs are not to be used in pressure applications for safety and environmental reasons. **SAFETY ALERT**

Polypropylene Adapter Elbows

90° Adapter x Female NPT



Size	Polypropylene Part #	Price/E	Pkg Qty
1½"	90PPA150	\$9.25	24
2"	90PPA200	10.15	24

90° Adapter x Male NPT



Size	Polypropylene Part #	Price/E	Pkg Qty
1½"	90PPF150	\$10.70	24
2"	90PPF200	11.50	24

- Recommended for a maximum working pressure of **100 PSI** (1½" - 2"). Recommendations based on the use of mating Dixon fittings at an ambient temperature of **70°F** with standard seal installed.
- Adapter elbows are manufactured from a glass-filled polypropylene.
- For use at elevated temperatures or other unusual operating conditions, consult factory. **SAFETY ALERT**

Optional Pkg./Box Quantity Shown