


Boss Couplings

Boss Clamps

C
Boss
Fittings



2-Bolt Type



**4-Bolt Type
2 Gripping Fingers**



**4-Bolt Type
4 Gripping Fingers¹**

Hose I.D.	Hose O.D.		Plated Iron			Stainless Steel			Brass		
	From:	To:	Part #	Price/E	Qty	Part #	Price/E	Torque ³	Part #	Price/E	Torque
1/4"	36/64"	42/64"	BD⁴	\$7.50	100	---	---	6	---	---	---
3/8"	44/64"	56/64"	CD⁴	6.80	100	---	---	6	---	---	---
1/2"	52/64"	60/64"	DD⁴	7.95	100	---	---	6	---	---	---
1/2"	60/64"	1-4/64"	B4⁴	6.85	25	RB4	\$131.30	12	BB4	\$24.00	10
1/2"	1-4/64"	1-12/64"	B5⁴	7.85	25	---	---	12	---	---	---
3/4"	1-10/64"	1-20/64"	BU9⁴	8.60	50	RBU9	175.10	21	BBU9	30.75	18
3/4"	1-20/64"	1-32/64"	B9	9.00	25	RB9	175.10	21	BB9	31.90	18
3/4"	1-32/64"	1-44/64"	B10⁴	10.90	25	---	---	21	BB10	30.00	---
1/2"	58/64"	1-2/64"	968	12.25	50	---	---	6	---	---	---
1"	1-26/64"	1-36/64"	156^{1, 4}	15.60	20	---	---	21	---	---	---
1"	1-34/64"	1-46/64"	BU14	15.75	25	RBU14	178.00	21	BBU14	67.60	18
1"	1-44/64"	1-60/64"	B14⁴	16.00	25	RB14	178.00	21	BB14	82.15	18
1"	1-60/64"	2-8/64"	B15	17.50	20	---	---	21	---	---	---
1-1/4"	1-32/64"	1-50/64"	BU18	25.60	10	---	---	40	---	---	---
1-1/4"	1-44/64"	1-56/64"	187¹	22.60	10	---	---	21	---	---	---
1-1/4"	1-50/64"	2-6/64"	BU19	28.10	10	---	---	40	---	---	---
1-1/4"	1-56/64"	2-4/64"	206¹	19.90	20	---	---	21	---	---	---
1-1/4"	2-8/64"	2-24/64"	B19	23.00	10	RB19	184.00	40	BB19²	115.00	28
1-1/2"	1-52/64"	2"	BU22	28.70	10	---	---	40	---	---	---
1-1/2"	2"	2-14/64"	B22	27.25	10	---	---	40	---	---	---
1-1/2"	2"	2-8/64"	212¹	26.00	10	---	---	21	---	---	---
1-1/2"	2-4/64"	2-16/64"	225¹	27.00	10	---	---	40	---	---	---
1-1/2"	2-12/64"	2-24/64"	BU24	23.60	10	RBU24	193.00	40	BBU24²	116.00	28
1-1/2"	2-24/64"	2-36/64"	B24	21.65	10	RB24	185.00	40	---	---	---
1-1/2"	2-36/64"	2-48/64"	B25	25.00	10	---	---	40	---	---	---
2"	2-16/64"	2-32/64"	250^{1, 5}	28.20	10	---	---	40	---	---	---
2"	2-22/64"	2-34/64"	BU28	32.70	10	---	---	60	---	---	---
2"	2-32/64"	2-48/64"	275^{1, 5}	32.00	10	---	---	40	---	---	---
2"	2-32/64"	2-50/64"	BU29	29.10	10	RBU29	287.00	60	BBU29²	116.00	40
2"	2-48/64"	3-4/64"	B29	32.20	10	RB29	287.00	60	BB29²	115.00	40
2"	2-48/64"	3-4/64"	306^{1, 5}	38.75	10	---	---	60	---	---	---
2"	3-6/64"	3-28/64"	B30	54.00	5	---	---	60	---	---	---
2-1/2"	3-4/64"	3-32/64"	350¹	40.60	5	---	---	60	---	---	---
2-1/2"	3-6/64"	3-28/64"	BU34	57.25	5	---	---	60	---	---	---
2-1/2"	3-32/64"	3-60/64"	B34	70.45	5	---	---	150	---	---	---
3"	3-32/64"	3-48/64"	375¹	51.00	5	---	---	60	---	---	---
3"	3-32/64"	3-60/64"	BU35	85.00	5	RBU35	420.00	150	---	---	---
3"	3-48/64"	4"	401¹	92.75	5	---	---	150	---	---	---
3"	3-52/64"	4-4/64"	B35	75.40	5	---	---	150	---	---	---
3"	4"	4-12/64"	418¹	99.50	4	---	---	200	---	---	---
3"	4-4/64"	4-28/64"	B39	97.95	5	---	---	200	---	---	---
3"	4-12/64"	4-32/64"	450¹	90.25	2	---	---	200	---	---	---

¹ 4 gripping fingers

² Will become obsolete as inventory is depleted.

³ Torque applies to plated iron *and* stainless steel clamps

⁴ Investment cast carbon steel

⁵ Not to be used with GF81, GB26, WF81, B26, RGF81, RGB26, BGF81, BGB26, RWF81, RB26

- Replacement nuts and bolts are available, contact the factory for more information.
- The bolts used in the Boss interlocking clamps are not standard bolts. They vary from standard bolts in their length, diameter, overall thread length and material hardness. These bolts can be retorqued, but it is **not** recommended that the bolts or clamps be reused, as they are designed for a single bend only. Dixon recommends using only factory supplied replacement bolts.
- Torque values for clamps are based on dry bolts. The use of lubricant on bolts will adversely effect clamp performance. *Do not lubricate nuts and bolts.*
- See page 519 for Fraction to Decimal conversion chart.
- Recommended torque rating in ft. lbs.

**SAFETY
ALERT**

**SAFETY
ALERT**

**SAFETY
ALERT**

Optional Pkg./Box Quantity Shown