

Air King Accessories

SAFETY
ALERT

Air King is for air and water service only

SAFETY
ALERT

The use of an Air King safety clip or wire type retainer is necessary to ensure Air King universal couplings will not become accidentally disconnected. This guarantees the fittings are properly connected as the pin will not go through the holes in the mating flanges until couplings are locked in place. Only one Air King safety clip or wire type retainer is required for each Air King universal coupling.

Standard Safety Clip



- Same size for all coupling sizes

Wire Diameter	Part #	Price/E
.080	AC1	\$.25

Sold only in bags of 25

Air King Safety Pins



- Heavy duty
- Oversized

Wire Diameter	Part #	Price/E
.058	AKSP1	\$1.10
.091	AKSP25	1.35

Stainless Steel Clip



- Same size for all coupling sizes

Wire Diameter	Part #	Price/E
.072	AC7	\$1.65

Lanyards



- Synthetic cord
- Same size for all coupling sizes

Part #	Price/E
ACL8	\$.30


Sold only in bags of 25



- Stainless steel cable

Part #	Price/E
LR7	\$5.90

Washers



- Same size for all coupling sizes
- Rubber temperature range: -20°F to 160°F
- Neoprene temperature range: -20°F to 190°F
- Neoprene is oil resistant

Black natural rubber		Neoprene	
Part #	Price/E	Part #	Price/E
AWR4	\$.45	AWS6	\$.65

Sold only in bags of 50

Air King Clamps



Size	Hose O.D.		Torque ¹	Plated Iron		Pkg Qty
	From:	To:		Part #	Price/E	
3/8"	44/64"	56/64"	6	CD³	\$6.80	100
1/2"	1"	1-12/64"	6	A4	6.85	50
3/4"	1-8/64"	1-20/64"	12	A9³	7.70	50
1"	1-20/64"	1-32/64"	12	A10^{2,3}	10.90	50
1"	1-32/64"	1-52/64"	21	A14	13.70	50

¹ Recommended torque rating in ft. lbs

² Can be used with **AM6** and **AM11**

³ Investment cast carbon steel

Note: Torque values for clamps are based on dry bolts.

The use of lubricant on bolts will adversely effect clamp performance.

Optional Pkg./Box Quantity Shown

SAFETY
ALERT

Warning: Never use any Air King coupling for steam service!

None of Dixon's catalog information is to be interpreted to mean that this type of coupling is suitable for use on steam hose.