

## King Safety Cables

**SAFETY  
ALERT**

When hose, couplings or clamps fail, or there is an accidental separation of the assembly, King safety cables minimize damage to equipment and injuries to operators. King safety cable reaches across the hose fittings to provide standby safety for hose. Spring-loaded loops in the cable ends open easily to pass over the couplings for a firm grip on the hose. Thoroughly tested with years of service. A positive safeguard for air hose connections - helps you meet today's safety standards. *King safety cable must be installed in the extended position (no slack).*

### Features:

- Hose-to-hose or hose-to-rigid outlet
- King cable is the low cost answer to eliminate injuries caused by broken air hose connections
- Highly resistant to rust and corrosion
- No tools needed - Easy to install and remove

**D**  
Air Fittings



**Style WSR, for hose-to-tool service**

Cable	Part #	Hose I.D.	Length	Max. Working Pressure PSI	Price/E
1/8"	<b>WSR1</b>	1/2" to 1 1/4"	20 1/4"	200	\$17.20
3/16"	<b>WSR3</b>	1/2" to 2"	28"	200	24.70
1/4"	<b>WSR2</b>	1 1/2" to 3"	38"	200	27.15
3/8"	<b>WSR4</b>	4"	44"	200	60.15



**Style W, for hose-to-hose service**

Cable	Part #	Hose I.D.	Length	Max. Working Pressure PSI	Price/E
1/8"	<b>WB1</b>	1/2" to 1 1/4"	20-1/4"	200	\$17.20
3/16"	<b>WB3</b>	1/2" to 2"	28"	200	25.50
1/4"	<b>WA2</b>	1 1/2" to 3"	38-1/4"	200	28.00
3/8"	<b>WA4</b>	4"	44"	200	60.15

**Note:** Cables are shipped with safety restraint labels attached. Labels are not pictured.

## King Safety Cable Options



**WSR1E**

WSR1E with stainless steel marine eye



**WB1C**

WB1 with safety clip and lanyard

Cable	Part #	Description	Max. Working Pressure PSI	Price/E
1/8"	<b>WSR1C</b>	WSR1 with safety clip and lanyard used to lock Air King couplings	200	\$29.95
1/8"	<b>WB1C</b>	WB1 with safety clip and lanyard used to lock Air King couplings	200	29.40
1/8"	<b>WSR1E</b>	WSR1 with stainless steel safety marine eye used to connect safety cable to a bolt on tool	200	49.65
1/4"	<b>WA2B</b>	WA2 with bronze/copper ferrule for special environmental conditions	200	56.10
1/8"	<b>WB1SS</b>	WB1 made with 304 stainless steel cable and springs with bronze/copper ferrules for special environmental conditions	200	47.25

## OSHA Regulations

### Standards - 29 CFR, 1915.131 (partial):

(e) Before use, pneumatic tools shall be secured to the extension hose or whip by some positive means to prevent the tool from becoming accidentally disconnected from the whip.

### Standards - 29 CFR, 1926.302 (partial):

(b)(1) Pneumatic power tools shall be secured to the hose or whip by some positive means to prevent the tool from becoming accidentally disconnected.

### Standards - 29 CFR, 1926.603 (partial):

(a)(9) Steam hose leading to a steam hammer or jet pipe shall be securely attached to the hammer with an adequate length of at least 1/4-inch diameter chain or cable to prevent whipping in the event the joint at the hammer is broken. Air hammer hoses shall be provided with the same protection as required for steam lines.

(a)(10) Safety chains, or equivalent means, shall be provided for each hose connection to prevent the line from thrashing around in case the coupling becomes disconnected.

The regulations may be viewed in full on the OSHA website, <http://www.osha.gov>. Please check the website for updates.

The **Canada Occupational Safety and Health** regulations, Part XIII, 13:6b states:

"Where an air hose is connected to a portable air powered tool used by an employee, a restraining device shall be attached to all hose connections, in order to prevent injury to an employee in the event of an accidental disconnection of a hose."