



Air Fittings and Accessories

Dixon Keychain



- Halves separate like a coupler and plug

Part #	Plated Steel	Price/E
DKC1		\$15.35

Breather Vents

D
Air Fittings

Breather vents have many applications, including vacuum relief or pressure equalization on gear boxes, oil tanks or reservoirs. Common uses can be found on single acting cylinders or valves to prevent dirt and foreign particles from entering ports open to the atmosphere.

- Nickel plated steel insert with a bronze filter
- Standard pipe thread fittings for quick assembly and removal for cleaning
- Maximum operating pressure: **150 PSI**
- Operating temperatures: **35°F to 300°F**
- The filter element is rated for 40 micron filtration.



NPT Thread Size	Overall Length	Nickel Plated Steel Part #	Price/E
1/8"	7/16"	ASP-1BV	\$1.95
1/4"	5/8"	ASP-2BV	2.15
3/8"	3/4"	ASP-3BV	3.05
1/2"	7/8"	ASP-4BV	4.40
3/4"	1"	ASP-6BV	6.95
1"	1-5/16"	ASP-8BV	14.10

Conical Mufflers

Conical mufflers are easy to install, threading the exhaust ports of air tool, valves, cylinders and other pneumatic equipment. They offer an economical method of reducing the noise levels below 90 dBA, conforming with OSHA standards.

- The bronze filter element is rated for 40 micron filtration. The element is bonded directly to the fitting.
Note: These elements are not replaceable.
- Maximum operating pressure: **300 PSI**
- Operating temperature: **35°F to 300°F**




NPT Thread Size	Overall Length	Nickel Plated Steel Part #	Price/E
1/8"	29/32"	CMF18	\$3.60
1/4"	1-1/4"	CMF28	4.30
3/8"	1-9/16"	CMF38	5.60
1/2"	1-13/16"	CMF48	6.80
3/4"	2-1/8"	CMF68	11.20
1"	2-7/8"	CMF88	16.45

Speed Control Mufflers

Speed control mufflers provide an infinite variation of metering air flow at an acceptable sound level on exhaust ports of air valves with complete safety. The speed of an operating cylinder or air tool may be increased or decreased with the adjusting screw. The final position is then locked in place by the lock nut. Objectionable exhaust air noise is eliminated by the surrounding sleeve of sintered bronze.

- Maximum operating pressure: **300 PSI**
- Operating temperature: **35°F to 300°F**



NPT Thread Size	Approx. Full Oper. Height	Maximum Adjusted SCFM	Brass Part #	Price/E
1/8"	1-5/16"	20	SCM18	\$5.50
1/4"	1-9/16"	30	SCM28	6.35
3/8"	1-5/8"	40	SCM38	9.25
1/2"	2"	60	SCM48	14.25
3/4"	2-3/8"	70	SCM68	18.90
1"	2-1/2"	100	SCM88	30.60