



## Hose Reels and Racks

### Reelcraft® 5000 Series Spring Driven Hose Reels

#### With Hose

Hose I.D.	Hose Length	Service	PSI	Weight lbs.	Part #	Price/E
1/4"	50'	air / water	300	26	5450LP	\$594.00
3/8"	35'	air / water	300	25	5635LP	565.90
3/8"	50'	air / water	300	37	5650LP	674.00

#### Without Hose

Hose Capacity	Service	PSI	Weight lbs.	Part #	Price/E
50' of 1/4" or 35' of 3/8"	air / water	500	21	5600LP	\$487.00
50' of 3/8"	air / water	500	31	5605LP	561.00



D  
Air Fittings

- Maximum temperature is 150°F
- Reel inlet 3/8" NPTF
- All steel construction
- Full shaft and swivel
- Furnished standard with PVC hose
- Compressed air hose should not be converted to oxygen service. Compressed air hoses are often contaminated with an oil coating, which can react explosively when oxygen is introduced.

### Reelcraft® 7000 Series Spring Driven Hose Reels

#### With Hose

Hose I.D.	Hose Length	Service	PSI	Weight lbs.	Part #	Price/E
3/8"	70'	air / water	300	50	7670LP	\$901.00
1/2"	50'	air / water	300	51	7850LP	890.00

#### Without Hose

Hose Capacity	Service	PSI	Weight lbs.	Part #	Price/E
70' of 3/8", 50' of 1/2"	air / water	500	43	7800LP	\$710.00
50' of 3/8" or 50' of 1/2"	oil	3000	44	7800MP	820.00
50' of 1/4" or 50' of 3/8"	grease	5000	46	7600HP	948.00



- All steel construction
- "LP" Low Pressure reels:  
Maximum temperature 150°F  
Reel inlet 1/2" NPTF  
PVC hose is standard
- "MP" Medium Pressure reels:  
Maximum temperature 210°F  
Reel inlet 1/2" NPTF  
SAE 100 R1T 1-wire braid hose standard
- "HP" High Pressure reels:  
Maximum temperature 210°F  
Reel inlet 1/4" NPTF  
SAE 100 R2T 2-wire braid hose standard

### Reelcraft® 80000 Series Spring Driven Hose Reels

#### With Hose

Hose I.D.	Hose Length	Service	PSI	Weight lbs.	Part #	Price/E
1/2"	75'	air / water	300	90	82075LP	\$1310.00
1/2"	100'	air / water	300	99	82100LP	1366.00
3/4"	50'	air / water	250	89	83050LP	1315.00

#### Without Hose

Hose Capacity	Service	PSI	Weight lbs.	Part #	Price/E
50' of 3/4" or 100' of 1/2"	air / water	500	74	83000LP	\$1156.00



- Maximum temperature is 150°F with hose
- Maximum temperature is 210°F without hose
- Furnished standard with PVC hose
- Reel inlet 3/4" NPTF
- Five-in-one heat treated aluminum casting incorporates main shaft, ratchet, spring arbor and inlet/outlet plumbing in one piece casting. High pressure cast steel.
- The most compact 3/4" x 50' hose reel of its capacity available.

See next page for bumper stops.  
Consult factory for uses  
other than stated services.