

Push-In Fittings

Legris Nickel-Plated Brass Push-In Fittings



**Equal Unions
(Tube to Tube)**

| Tube O.D. | Brass Part # | Price/E | Pkg Qty |
|-----------|-----------------|---------------|---------|
| 5/32" | 32060400 | \$5.85 | 10 |
| 1/4" | 32065600 | 6.65 | 10 |
| 3/8" | 32066000 | 13.25 | 10 |
| 1/2" | 32066200 | 13.90 | 10 |



**Union Elbows
(Tube to Tube)**

| Tube O.D. | Brass Part # | Price/E | Pkg Qty |
|-----------|-----------------|---------------|---------|
| 5/32" | 32020400 | \$5.65 | 10 |
| 1/4" | 32025600 | 6.10 | 10 |
| 3/8" | 32026000 | 11.20 | 10 |
| 1/2" | 32026200 | 14.55 | 10 |



**Union Tees
(Tube to Tube)**

| Tube O.D. | Brass Part # | Price/E | Pkg Qty |
|-----------|-----------------|---------------|---------|
| 5/32" | 32040400 | \$7.35 | 10 |
| 1/4" | 32045600 | 8.30 | 10 |
| 3/8" | 32046000 | 14.55 | 10 |
| 1/2" | 32046200 | 18.50 | 10 |

Legris Nylon/Nickel-Plated Brass Push-In Fittings

Materials: Nickel-plated brass construction. Black body is glass-filled nylon; Buna-N O-ring seal; polypropylene release button. Silicone free.

Positive Seal: sealing and holding is accomplished instantaneously

Reusable: connect and disconnect numerous times

Full Flow: fitting seals on outside diameter of tubing

Working Pressure: fittings rated to **290 PSI** at ambient temperature

Working Temperature: **-4°F to 175°F**

SAFETY ALERT Maximum circuit pressure depends equally on the type and diameter of the tube used.

Pre-applied thread sealant on all male pipe threads

Compatible Tubing: semi-rigid nylon, polyurethane and polyethylene tube

Vacuum Capability: vacuum of 28" Hg (99% vacuum)

Gripping Ring Technology



Quick Connect and Disconnect: Simply push tubing in. To remove, press the release ring towards the fitting and pull tubing out. No tools required.



**Male Swivel Branch Tees
(Tube to Male NPT)**

| Tube O.D. | Male NPT | Plated Brass Part # | Price/E | Pkg Qty |
|-----------|----------|---------------------|---------------|---------|
| 1/8" | 10-32 * | 31085320 | \$9.70 | 10 |
| 1/8" | 1/8" | 31085311 | 7.25 | 10 |
| 5/32" | 10-32 * | 31080420 | 10.35 | 10 |
| 5/32" | 1/8" | 31080411 | 6.80 | 10 |
| 5/32" | 1/4" | 31080414 | 10.05 | 10 |
| 1/4" | 1/8" | 31085611 | 6.05 | 10 |
| 1/4" | 1/4" | 31085614 | 6.65 | 10 |
| 1/4" | 3/8" | 31085618 | 8.10 | 10 |
| 5/16" | 1/8" | 31080811 | 9.45 | 10 |
| 5/16" | 1/4" | 31080814 | 9.80 | 10 |
| 5/16" | 3/8" | 31080818 | 10.05 | 10 |
| 3/8" | 1/8" | 31086011 | 12.85 | 10 |
| 3/8" | 1/4" | 31086014 | 9.45 | 10 |
| 3/8" | 3/8" | 31086018 | 10.95 | 10 |
| 3/8" | 1/2" | 31086022 | 14.25 | 10 |
| 1/2" | 1/4" | 31086214 | 12.35 | 10 |
| 1/2" | 3/8" | 31086218 | 15.40 | 10 |
| 1/2" | 1/2" | 31086222 | 17.40 | 10 |

* UNF - Straight thread, supplied with gasket



**Male Swivel Run Tees
(Tube to Male NPT)**

| Tube O.D. | Male NPT | Plated Brass Part # | Price/E | Pkg Qty |
|-----------|----------|---------------------|---------------|---------|
| 1/8" | 10-32 * | 31035320 | \$9.80 | 10 |
| 1/8" | 1/16" | 31035308 | 10.05 | 10 |
| 1/8" | 1/8" | 31035311 | 7.60 | 10 |
| 5/32" | 10-32 * | 31030420 | 10.65 | 10 |
| 5/32" | 1/8" | 31030411 | 7.50 | 10 |
| 5/32" | 1/4" | 31030414 | 10.35 | 10 |
| 1/4" | 1/8" | 31035611 | 6.15 | 10 |
| 1/4" | 1/4" | 31035614 | 6.65 | 10 |
| 1/4" | 3/8" | 31035618 | 8.15 | 10 |
| 5/16" | 1/8" | 31030811 | 9.20 | 10 |
| 5/16" | 1/4" | 31030814 | 9.70 | 10 |
| 3/8" | 1/8" | 31036011 | 12.40 | 10 |
| 3/8" | 1/4" | 31036014 | 10.35 | 10 |
| 3/8" | 3/8" | 31036018 | 11.50 | 10 |
| 3/8" | 1/2" | 31036214 | 12.55 | 10 |
| 1/2" | 3/8" | 31036218 | 15.40 | 10 |
| 1/2" | 1/2" | 31036222 | 17.10 | 10 |

* UNF - Straight thread, supplied with gasket