
Wilkerson Regulators






Standard

With Gauge				Without Gauge			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
3/8"	R28-03RG	120	\$124.40	3/8"	R28-03R	120	\$109.25
1/2"	R28-04RG	135	124.40	1/2"	R28-04R	135	109.25
3/4"	R28-06RG	125	124.40	3/4"	R28-06R	125	109.25





- 0-125 PSI range
- Balanced valve design
- Maximum operating conditions: 300 PSIG (21 bar) and 175°F (79°C)




High Flow

		riight flow						
With Gauge				Without Gauge				
	Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
	3/4"	R30-06RG	480	\$230.75	3/4"	R30-06R	480	\$215.60
	1"	R30-08RG	500	230.75	1"	R30-08R	500	215.60
	1-1/4"	R30-0ARG	800	230.75	1-1/4"	R30-0AR	800	215.60







High Flow

With Gauge					Without Gauge			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E	
1-1/2"	R40-0BRG	1200	\$421.60	1-1/2"	R40-0BR	1200	\$406.45	
2"	R40-0CRG	1200	421.60	2"	R40-0CR	1200	406.45	

- 0-125 PSI range
- Self-relieving standard
- Heavy duty spring
- Balanced valve design
- Piston operated
- Two 1/4" NPT gauge ports standard can be used for additional outlet ports
- Maximum operating conditions: 300 PSIG (21 bar) and 150°F (65.5°C)

All models with gauges on this page are supplied with a GC230 standard gauge.

SCFM ratings at 150 PSIG inlet pressure.

DPL108 167



