Wilkerson Filter / Regulators

Standard Transparent Bowl with Guard







Standard Metal Bowl with Sight Glass

Automatic Drain				Manual Drain			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
3/8"	B28-03AGMB	140	\$266.95	3/8"	B28-03MGMB	140	\$216.35
1/2"	B28-04AGMB	150	266.95	1/2"	B28-04MGMB	150	216.35
3/4"	B28-06AGMB	165	266.95	3/4"	B28-06MGMB	165	216.35


- High flow capacity
- 0-125 PSIG (0-8.5 bar)
- 5 micron filter
- 6 oz. bowl
- Balanced valve design
- Spring-loaded diaphragm

Maximum operating conditions: Transparent bowls:

150 PSIG (10 bar) and 125°F (52°C)

Metal bowls:


250 PSIG (17 bar) and 175°F (79°C)







Designed so that all the oil flow observed in the sight dome is broken into a mist and delivered via the airflow to the application. This lubricator allows the user to fill or replenish the oil in the bowl without interrupting airflow or bleeding pressure from the system (except miniature models). Once the oil-fill cap is removed, the bowl is depressurized and isolated from line pressure, and the bowl itself can then be removed, if desired, for faster refill. The bowl can also be filled right to the top.






Size	Part #	SCFM	Price/E
1/4"	L16-02A	28	\$125.05
3/8"	L16-03A	48	125.05
1/2"	L16-04A	52	125.05

Compact Metal 5 oz. Bowl with Sight Glass

	Size	Part #	SCFM	Price/E			
	1/4"	L16-02AMB	28	\$141.40			
	3/8"	L16-03AMB	48	141.40			
	1/2"	L16-04AMB	52	141.40			



SCFM ratings at 150 PSIG inlet pressure.

170 **DPL108**

