Series 1 Airline Filters

Dixon FRL's are rugged and long lasting units for compressed air service, or water or gas service *if indicated*. Units may be purchased assembled or individually. Please consult Dixon for special service applications on these and all hose fittings.

1/4" Basic
Transparent Bowl

	Semi-Automatic Drain				Manual Drain		
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
1/4"	F72G-2A	55	$104.15	1/4"	F72G-2M	55	$57.85
3/8"	F72G-3A	55	106.85	3/8"	F72G-3M	55	60.70

0.75 (19)
7.27 (185)
5.27 (134)

† Minimum clearance required to remove bowl.

1/4" Basic
Metal Bowl with Sight Glass

	Semi-Automatic Drain				Manual Drain		
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
1/4"	F72G-2A-MB	55	$116.85	1/4"	F72G-2M-MB	55	$70.55
3/8"	F72G-3A-MB	55	119.55	3/8"	F72G-3M-MB	55	73.35

- 2 oz. reservoir
- Quick-release bayonet bowl
- Prismatic lens liquid level indicator
- 40 micron filter element standard
- Particle removal per ISO 8573-1, Class 5 and Class 3
- Inlet pressure for transparent bowl is **150 PSI**
- Inlet pressure for metal bowl is **250 PSI** maximum

0.75 (19)
7.27 (185)
5.27 (134)

† Minimum clearance required to remove bowl.

3/8" Basic
Transparent Bowl

	Automatic Drain				Manual Drain		
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
1/4"	F73G-2A	53	$147.80	1/4"	F73G-2M	53	$90.25
3/8"	F73G-3A	65	147.80	3/8"	F73G-3M	65	90.25
1/2"	F73G-4A	69	147.80	1/2"	F73G-4M	69	90.25

2.68 (68)
8.50 (216)
6.15 (156)

** Minimum clearance required to remove bowl.

3/8" Basic
Metal Bowl with Sight Glass

	Automatic Drain				Manual Drain		
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
1/4"	F73G-2A-MB	53	$154.95	1/4"	F73G-2M-MB	53	$97.60
3/8"	F73G-3A-MB	65	154.95	3/8"	F73G-3M-MB	65	97.60
1/2"	F73G-4A-MB	69	154.95	1/2"	F73G-4M-MB	69	97.60

- 4 oz. reservoir
- Quick-release bayonet bowl
- Prismatic lens liquid level indicator
- 40 micron filter element standard
- Particle removal per ISO 8573-1, Class 5 and Class 3
- Inlet pressure for transparent bowl is **150 PSI**
- Inlet pressure for metal bowl is **250 PSI** maximum

2.68 (68)
8.50 (216)
6.15 (156)

1/4 Turn Manual Drain

** Minimum clearance required to remove bowl.

SCFM ratings at 100 PSI inlet pressure