

Series 1 Micro-Fog Lubricators


- Micro-fog lubricators, identified by a red adjusting screw, are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.
- Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.
- The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.
- Micro-fog lubricators *cannot* be filled under pressure.

1/4" Basic Transparent Bowl

Size	Part #	SCFM	Price/E
1/4"	L72M-2	51	\$90.55
3/8"	L72M-3	51	94.00

1/4" Basic Metal Bowl with Sight Glass

Size	Part #	SCFM	Price/E
1/4"	L72M-2MB	51	\$104.80
3/8"	L72M-3MB	51	108.10



** minimum clearance required to remove bowl

- 2 oz. reservoir
- In-line or modular installation
- Micro-fog design delivers aerosol mist
- Quick release bayonet bowl
- Inlet pressure for transparent bowl is **150 PSI**
- Inlet pressure for metal bowl is **250 PSI**
- Maximum temperature for transparent bowl is **125°F**
- Maximum temperature for metal bowl is **175°F**
- Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at **100°F**





D
Air
Fittings

3/8" Basic Transparent Bowl

Size	Part #	SCFM	Price/E
1/4"	L73M-2	70	\$111.20
3/8"	L73M-3	70	111.20
1/2"	L73M-4	70	111.20

3/8" Basic Metal Bowl with Sight Glass

Size	Part #	SCFM	Price/E
1/4"	L73M-2MB	70	\$118.55
3/8"	L73M-3MB	70	118.55
1/2"	L73M-4MB	70	118.55



- 4 oz. reservoir
- In-line or modular installation
- Micro-fog design delivers aerosol mist
- Quick release bayonet bowl
- Inlet pressure for transparent bowl is **150 PSI**
- Inlet pressure for metal bowl is **250 PSI**
- Maximum temperature for transparent bowl is **125°F**
- Maximum temperature for metal bowl is **175°F**
- Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at **100°F**



SCFM ratings at 100 PSI inlet pressure