


Series 1 Combination Units

1/2" Basic - Transparent Bowl with Guard




Automatic Drain				Manual Drain			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
3/8"	E74-3A	110	\$627.25	3/8"	E74-3M	110	\$569.60
1/2"	E74-4A	150	627.25	1/2"	E74-4M	150	569.60
3/4"	E74-6A	140	627.25	3/4"	E74-6M	140	569.60



D
Air
Fittings

1/2" Basic - Metal Bowl with Sight Glass




Automatic Drain				Manual Drain			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
3/8"	E74-3A-MB	110	\$634.65	3/8"	E74-3M-MB	110	\$577.30
1/2"	E74-4A-MB	150	634.65	1/2"	E74-4M-MB	150	577.30
3/4"	E74-6A-MB	140	634.65	3/4"	E74-6M-MB	140	577.30

Metal bowl pictured

- Connected modularly
- Includes 2 clamp and wall mounting brackets #4314-52, 2 clamps #4314-51 and 2 NPT pipe adapters. See modular components on pages 200-201 for other options.
- 7 oz. reservoir
- Adjustable **5-150 PSI**
- Inlet pressure for transparent bowl is **150 PSI**
- Inlet pressure for metal bowl is **250 PSI** maximum

1" Basic - Metal Bowl with Sight Glass



Automatic Drain				Manual Drain			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
3/4"	P8A-660A	160	\$896.95	3/4"	P8A-660M	160	\$839.70
1"	P8A-860A	275	891.65	1"	P8A-860M	275	834.40



- 1 qt. reservoir
- Adjustable **5-125 PSI**
- Inlet pressure **250 PSI** maximum

These units are intended for use in industrial compressed air systems only. They must not be used where pressure or temperature may exceed maximum rated operating conditions. See specifications. The polycarbonated plastic bowls used on these units can be damaged and possibly burst if exposed to such substances as certain solvents, strong alkalis, compressor oils that contain ester-based additives or synthetic oils. Fumes of these substances in contact with the polycarbonate bowl, externally or internally, can also result in damage. Clean with warm water only. Use metal bowl in applications where a plastic bowl might be exposed to substances that are incompatible with polycarbonates. Not for use with fluids. Combination Units are supplied with micro-fog lubricators.

SCFM ratings at 100 PSI inlet pressure