



Gauges

ABS Standard Dry Gauges

- ASME B40.1, Grade B (+/- 3-2-3% accuracy)
- ABS plastic case
- C-shaped bronze safety bourdon tube (**600 PSI** and lower)
- helical wound bronze safety bourdon tube (**1000 PSI** and higher)
- polycarbonate crystal
- black aluminum pointer
- PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.
- ambient temperature range of - 40°F to 150°F

Center Back Mount Standard Dry Gauges

1½" face
1/8" center back mount

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-30	5	.5	GC605	\$14.45
0-60	5	1	GC610	14.45
0-100	10	2	GC615	14.45
0-160	20	5	GC620	14.45
0-200	20	5	GC625	14.45

2" face
1/4" center back mount

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GC200	\$15.15
0-30	5	.5	GC215	15.15
0-60	5	1	GC220	15.15
0-100	10	2	GC225	15.15
0-160	20	5	GC230	15.15
0-200	20	5	GC235	15.15
0-300	30	5	GC240	15.15



GC200

Lower Mount Standard Dry Gauges

2" face
¼" lower mount

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GL100	\$13.00
0-30	5	.5	GL115	13.00
0-60	5	1	GL120	13.00
0-100	10	2	GL125	13.00
0-160	20	5	GL130	13.00
0-200	20	5	GL135	13.00
0-300	30	5	GL140	13.00



GL135

2½" face
¼" lower mount

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GL300	\$14.25
0-30	5	.5	GL320	14.25
0-60	5	1	GL325	14.25
0-100	10	2	GL330	14.25
0-160	20	5	GL335	14.25
0-200	20	5	GL340	14.25
0-300	30	5	GL345	14.25
0-400	50	10	GL347	14.25
0-600	50	10	GL350	14.25
0-1000	200	20	GL355	23.25
0-1500	300	50	GL360	23.25
0-2000	400	50	GL365	23.25
0-3000	500	100	GL370	23.25
0-5000	1000	100	GL375	23.25

3½" face
¼" lower mount

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GS15-4	\$19.35
0-30	5	.5	GS30-4	19.35
0-60	5	1	GS60-4	19.35
0-100	10	2	GS100-4	19.35
0-160	20	5	GS160-4	19.35
0-200	20	5	GS200-4	19.35
0-300	30	5	GS300-4	19.35
0-400	50	10	GS400-4	19.35
0-600	50	10	GS600-4	19.35
0-1000	200	20	GS1000-4	29.15

D
Air
Fittings