

## Gauges

### All Stainless Steel Dry Gauges

Stainless steel gauges provide the corrosion resistance and durability of a permanently sealed gauge. Designed for severe service applications.



**2 1/2" face**  
1/4" lower mount

- 3-2-3% accuracy
- 316 series stainless steel solid back case with polycarbonate window
- 1/4" lower mount stainless steel connector
- 316 stainless steel bourdon tube and socket, polyester segment
- ambient temperature range of -40°F to 140°F



**3 1/2" face**  
1/4" lower mount

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	3	.2	<b>GSS15</b>	\$91.20
0-30	5	.5	<b>GSS30</b>	91.20
0-60	10	1	<b>GSS60</b>	91.20
0-100	20	2	<b>GSS100</b>	91.20
0-160	20	2	<b>GSS160</b>	91.20
0-200	50	5	<b>GSS200</b>	91.20
0-300	50	5	<b>GSS300</b>	91.20
0-400	100	10	<b>GSS400</b>	91.20
0-600	100	10	<b>GSS600</b>	91.20
0-1000	200	20	<b>GSS1000</b>	91.20
0-1500	300	20	<b>GSS1500</b>	91.20
0-2000	500	50	<b>GSS2000</b>	91.20
0-3000	500	50	<b>GSS3000</b>	91.20
0-5000	1000	100	<b>GSS5000</b>	91.20
0-10000	2000	200	<b>GSS10000</b>	121.90

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	3	.5	<b>GSS15-4</b>	\$137.80
0-30	5	.5	<b>GSS30-4</b>	137.80
0-60	10	1	<b>GSS60-4</b>	137.80
0-100	20	2	<b>GSS100-4</b>	137.80
0-160	20	2	<b>GSS160-4</b>	137.80
0-200	40	5	<b>GSS200-4</b>	137.80
0-300	50	5	<b>GSS300-4</b>	137.80
0-400	50	10	<b>GSS400-4</b>	137.80
0-600	100	10	<b>GSS600-4</b>	137.80
0-1000	200	10	<b>GSS1000-4</b>	137.80
0-1500	200	20	<b>GSS1500-4</b>	137.80
0-2000	400	20	<b>GSS2000-4</b>	137.80
0-3000	500	50	<b>GSS3000-4</b>	137.80
0-5000	1000	100	<b>GSS5000-4</b>	137.80
0-10000	2000	200	<b>GSS10000-4</b>	151.60

### All Stainless Steel Liquid Filled Gauges

Stainless steel gauges provide the corrosion resistance and durability of a permanently sealed gauge. Designed for severe service applications.

- 2 1/2" 316 series stainless steel solid back case with polycarbonate window
- 1/4" lower mount stainless steel connector
- 316 stainless steel bourdon tube and socket, polyester segment
- glycerin filled
- ambient temperature range of 20°F to 140°F



**2 1/2" face**  
1/4" lower mount



**2 1/2" face**  
1/4" center back mount

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-100	20	2	<b>GLSSC100</b>	\$132.50
0-160	20	2	<b>GLSSC160</b>	132.50
0-200	50	5	<b>GLSSC200</b>	132.50

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	3	.2	<b>GLSS15</b>	\$97.55
0-30	5	.5	<b>GLSS30</b>	97.55
0-60	10	1	<b>GLSS60</b>	97.55
0-100	20	2	<b>GLSS100</b>	97.55
0-160	20	2	<b>GLSS160</b>	97.55
0-200	50	5	<b>GLSS200</b>	97.55
0-300	50	5	<b>GLSS300</b>	97.55
0-400	100	10	<b>GLSS400</b>	97.55
0-600	100	10	<b>GLSS600</b>	97.55
0-1000	200	20	<b>GLSS1000</b>	97.55
0-1500	300	20	<b>GLSS1500</b>	97.55
0-2000	500	50	<b>GLSS2000</b>	97.55
0-3000	500	50	<b>GLSS3000</b>	97.55
0-5000	1000	100	<b>GLSS5000</b>	97.55
0-10000	2000	200	<b>GLSS10000</b>	132.50