

### Water-Steam Washdown Station

Fail-safe mixing station, bronze, wall mounted, safely blends steam and cold water for hot water on demand. Should cold water fail, the steam is instantly shut-off. **150 PSI** maximum, **200°F** maximum. Note: Station is not supplied with hose and nozzle.


All units are furnished with the following:

- Control valves
- Dial thermometer
- In-line check valves
- 3/4" inlet and outlet
- Stainless steel hose rack
- Mounting plate and hardware

Part #	Price/E
<b>SWDS</b>	<b>\$3145.60</b>

#### Pressure Requirements

Steam Pressure		Water Pressure	
Minimum	Maximum	Minimum	Maximum
<b>80 PSI</b>	<b>150 PSI</b>	<b>50 PSI</b>	<b>80 PSI</b>



### Hot and Cold Water Mixing Station

Hot and cold water mixing station, bronze, wall mounted. **150 PSI** maximum, **200°F** maximum.

All units are furnished with the following:

- Control valves
- Dial thermometer (optional)
- In-line check valves
- 3/4" inlet and outlet
- Stainless steel hose rack
- Mounting bracket and hardware

Style	Part #	Price/E
1	<b>WDS1</b>	<b>\$1140.15</b>



F  
Brass  
Fittings

### Rack for Mixing Station

Designed to hold 50' of 3/4" heavy duty industrial grade hose

- Heavy duty stainless steel construction
- Heavy duty solid brass mounting crowns
- Stainless steel lag screws
- Supplied with mounting hardware

Part #	Price/E
<b>WDSR</b>	<b>\$198.00</b>



### Hot Water Washdown Hose

- Working pressure: **250 PSI**
- Temperature to: **200°F**
- 3/4" male, both ends
- White, wrapped Neoprene cover (.075" thick), braided textile reinforcement
- Smooth extruded Chlorobutyl tube
- Furnished with internal stainless steel spring guards at both ends

Size	Part #	Price/E
5/8" x 25'	<b>SWDSHOSE25</b>	<b>\$679.00</b>
5/8" x 50'	<b>SWDSHOSE50</b>	<b>1146.70</b>

