



Washdown Nozzles, Pressure Gun and Accessories

Hot Water Washdown Spray Nozzles

For low pressure cleaning and sanitation applications, such as food and dairy processing, tank and drum cleaning, pharmaceutical and chemical manufacturing and meat and poultry packing.



- Efficient design for operator comfort
- Variable spray pattern from solid stream to 50° hollow cone
- Hose connects at base of gun for easy maneuvering
- 1/2" Female NPT inlet
- Rubber coated handle protects hands from water temperatures to 150°F
- **12.5 GPM** flow capacity at **150 PSI**
- *Do not use with steam lines.*

Cover color	Brass		Aluminum	
	Part #	Price/E	Part #	Price/E
Black	BWSG	\$260.00	AWSG	\$274.25
White	BWSG-W	281.10	AWSG-W	293.50

Swivel Connectors for Washdown Spray Guns


F
Brass
Fittings

- Brass swivel body
- Stainless steel hose shank
- Brass connecting nut
- EPDM gasket connecting nut



Hose Shank

NPT	Hose I.D.	Part #	Price/E
1/2"	1/2"	BNS44	\$56.15
1/2"	3/4"	BNS64	56.15



GHT Thread

NPT	Female GHT	Part #	Price/E
1/2"	3/4"	BMAS974	\$56.15

Thermal-Gard™ Elevated Temperature Spray Nozzle

The Thermal-Gard™ elevated temperature spray nozzle protects the operator from extreme hot water temperatures that exceed the comfort zone of standard hot water nozzles. 3/8" Female NPT inlet. Black cover.



- Assembly includes required special rigid, stainless steel adapter, (3/8" male NPT x 1/2" female NPT).
- Thermal insulating sleeve reduces overall heat during elevated temperature conditions.
- Stainless steel lever handle is coated for additional thermal protection, and operator comfort.
- Lightweight aluminum alloy body reduces overall weight.
- Corrosion resistant body is anodized for additional corrosion protection.
- Recommended for water temperatures above 140°F to a maximum temperature of 200°F.
- **14 GPM** flow capacity
- Working pressure: **150 PSI**

Aluminum	
Part #	Price/E
AWSG-TG	\$355.80