

Turbo Nozzles

- 15° spray angle
- Operating pressure: **3625 PSI** maximum
- Temperatures to **195°F**

Part #	Description	Price/E
AL-TPR25-30	1/4" female inlet, yellow, 1.30 mm orifice	\$155.00
AL-TPR25-50	1/4" female inlet, green, 1.50 mm orifice	155.00
AL-TPR25-70	1/4" female inlet, red, 1.70 mm orifice	155.00




Straight Through Quick-Connect Fittings

Coupler

Part #	Description	Material	Price/E
STFC2	1/4 coupler x 1/4" female NPT	brass	\$8.49
STFC2SS	1/4 coupler x 1/4" female NPT	stainless steel	47.30
STMC2	1/4 coupler x 1/4" male NPT	brass	8.49
STMC2SS	1/4 coupler x 1/4" male NPT	stainless steel	49.00
STFC3	3/8 coupler x 3/8" female NPT	brass	9.68
STFC3SS	3/8 coupler x 3/8" female NPT	stainless steel	67.00
STMC3	3/8 coupler x 3/8" male NPT	brass	9.68
STMC3SS	3/8 coupler x 3/8" male NPT	stainless steel	61.45



Female




Male



Plug

Part #	Description	Material	Price/E
STFP2	1/4 plug x 1/4" female NPT	steel	\$2.78
STFP2B	1/4 plug x 1/4" female NPT	brass	4.00
STFP2SS	1/4 plug x 1/4" female NPT	stainless steel	14.70
STMP2	1/4 plug x 1/4" male NPT	steel	2.33
STMP2B	1/4 plug x 1/4" male NPT	brass	3.75
STMP2SS	1/4 plug x 1/4" male NPT	stainless steel	13.30
STFP3	3/8 plug x 3/8" female NPT	steel	3.25
STFP3B	3/8 plug x 3/8" female NPT	brass	5.05
STFP3SS	3/8 plug x 3/8" female NPT	stainless steel	17.60
STMP3	3/8 plug x 3/8" male NPT	steel	3.01
STMP3B	3/8 plug x 3/8" male NPT	brass	4.60
STMP3SS	3/8 plug x 3/8" male NPT	stainless steel	15.25



Female



Male

Unloader

- Operating pressure: **3650 PSI** maximum
- Temperatures to **190°F**
- GPM: **8 gallons** maximum
- Inlet: 2 each, 3/8" female
- Outlet: 3/8" female
- Bypass: 2 each, 3/8" female
- Gauge port: 1/4" female

Part #	Description	Price/E
AL606	Pressure regulating unloader valve automatically relieves pressure from pump at shut-off.	\$147.00



Braided Rubber Hose

Part #	Pressure PSI	Length	Inside Diameter	Male Swivel Inlet	Male Swivel Outlet	Price/E
AR503830SSP	3,000	50'	3/8"	3/8"	3/8"	\$222.60

