



## Clamps


### Double Bolt Clamps

A rugged, plated iron two-bolt clamp with machine bolts and hex nuts. Inner surface has dual gripping ridges. Bolt lugs are reinforced to prevent bending out of alignment. Torque values for clamps are based on dry bolts. The use of lubricant on bolts will adversely effect clamp performance.



**SAFETY  
ALERT**

**Consult Dixon when using  
double bolt clamps on  
helical wire hose.**



Double bolt clamp without saddles

Hose O.D. Range From: To:	Part #	Price/E	Pkg Qty	Torque *
1-8/64"	1-12/64"	<b>J48</b>	<b>\$5.65</b>	100 15
1-12/64"	1-24/64"	<b>J49</b>	<b>7.15</b>	50 21
1-28/64"	1-34/64"	<b>JX49</b>	<b>8.65</b>	25 21
1-40/64"	1-52/64"	<b>DL14</b>	<b>9.95</b>	25 40
1-48/64"	2-3/64"	<b>DL20</b>	<b>9.90</b>	25 27
2-7/64"	2-19/64"	<b>DL24 **</b>	<b>9.90</b>	25 27
2-20/64"	2-40/64"	<b>DL32 **</b>	<b>11.35</b>	25 40
2-32/64"	2-48/64"	<b>DL275</b>	<b>14.20</b>	25 40
2-48/64"	3-4/64"	<b>DL306</b>	<b>15.90</b>	20 60
3-4/64"	3-24/64"	<b>DL328</b>	<b>16.40</b>	20 60
3-16/64"	3-32/64"	<b>DL350</b>	<b>16.55</b>	20 60

Double bolt clamp with two saddles

Hose O.D. Range From: To:	Part #	Price/E	Pkg Qty	Torque *
3-32/64"	3-52/64"	<b>400</b>	<b>\$16.50</b>	25 40
3-50/64"	4-4/64"	<b>431</b>	<b>19.95</b>	20 40
4-2/64"	4-18/64"	<b>463</b>	<b>17.55</b>	20 40
4-16/64"	4-60/64"	<b>525</b>	<b>21.90</b>	10 60
4-32/64"	5-16/64"	<b>550</b>	<b>22.80</b>	10 60
5-8/64"	5-44/64"	<b>600</b>	<b>24.60</b>	10 60
5-44/64"	5-60/64"	<b>639</b>	<b>28.05</b>	10 60
5-60/64"	6-32/64"	<b>675</b>	<b>26.75</b>	10 60
6-32/64"	7-36/64"	<b>769</b>	<b>29.60</b>	10 60
7-44/64"	8-12/64"	<b>818</b>	<b>42.85</b>	5 125
8-16/64"	8-56/64"	<b>875</b>	<b>42.65</b>	5 125
8-60/64"	9-56/64"	<b>988</b>	<b>52.45</b>	5 125
9-60/64"	11-24/64"	<b>1125</b>	<b>82.30</b>	5 125
11-12/64"	13"	<b>1275</b>	<b>92.10</b>	3 125
12-12/64"	14"	<b>1360</b>	<b>147.85</b>	2 200
13-12/64"	15"	<b>1450</b>	<b>137.50</b>	2 200
15-4/64"	17-32/64"	<b>1700</b>	<b>171.80</b>	2 260

\* Recommended torque rated in ft. lbs.  
\*\* Investment carbon steel

**Note:** Measure hose O.D. accurately before ordering clamps.

Optional Pkg./Box Quantity Shown

Clamps H

### Single Bolt Clamps



Torque values for clamps are based on dry bolts. The use of lubricant on bolts will adversely effect clamp performance.

- plated iron

**Note:** Measure hose O.D. accurately before ordering clamps.

Hose O.D. Range From: To:	Part #	Price/E	Torque *
56/64"	1"	<b>2</b>	<b>\$13.70</b> 6
62/64"	1-8/64"	<b>3</b>	<b>16.45</b> 6
1-4/64"	1-12/64"	<b>4</b>	<b>16.45</b> 6
1-10/64"	1-16/64"	<b>5</b>	<b>16.45</b> 6
1-16/64"	1-24/64"	<b>6</b>	<b>16.45</b> 6
1-22/64"	1-28/64"	<b>7</b>	<b>17.70</b> 6
1-28/64"	1-36/64"	<b>8</b>	<b>17.70</b> 6
1-34/64"	1-44/64"	<b>9</b>	<b>17.70</b> 6
1-42/64"	1-48/64"	<b>10</b>	<b>17.70</b> 6
1-48/64"	1-56/64"	<b>11</b>	<b>18.20</b> 6
1-56/64"	2-2/64"	<b>12</b>	<b>18.20</b> 6
2"	2-8/64"	<b>13</b>	<b>18.20</b> 12
2-8/64"	2-18/64"	<b>14</b>	<b>19.15</b> 12
2-16/64"	2-26/64"	<b>15</b>	<b>19.35</b> 12

Hose O.D. Range From: To:	Part #	Price/E	Torque *
2-24/64"	2-32/64"	<b>16</b>	<b>\$19.35</b> 12
2-32/64"	2-40/64"	<b>17</b>	<b>19.60</b> 12
2-40/64"	2-56/64"	<b>18</b>	<b>21.20</b> 12
2-56/64"	3-4/64"	<b>19</b>	<b>21.20</b> 12
3-4/64"	3-16/64"	<b>20</b>	<b>21.20</b> 12
3-16/64"	3-28/64"	<b>21</b>	<b>23.90</b> 12
3-28/64"	3-40/64"	<b>22</b>	<b>23.90</b> 21
3-40/64"	3-52/64"	<b>23</b>	<b>30.30</b> 21
3-52/64"	4-8/64"	<b>24</b>	<b>30.30</b> 21
4-8/64"	4-20/64"	<b>25</b>	<b>31.30</b> 21
4-16/64"	4-32/64"	<b>26</b>	<b>32.80</b> 21
4-28/64"	4-40/64"	<b>27</b>	<b>33.30</b> 21
4-40/64"	4-56/64"	<b>X27</b>	<b>33.30</b> 21
4-56/64"	5-16/64"	<b>28</b>	<b>33.30</b> 21

\* Recommended torque rated in ft. lbs.