




Hydraulic Fittings


Straight Through Quick-Connect Fittings


These couplers and plugs have no internal valves, providing maximum flow with minimum pressure drop. Supplied with Buna-N gasket seal. Interchange with Parker-Hannifin SST/BST, Foster FST and Hansen ST couplings.



Warning: Do Not Disconnect with pressure in line.

Female Couplers	Body Size	NPT Thread Size	Material	Operating PSI	Part #	Price/E	Pkg Qty
	1/4"	1/4" - 18	brass	4500	STFC2	\$8.49	12
	3/8"	3/8" - 18	brass	2700	STFC3	9.68	12
	1/2"	1/2" - 14	brass	2500	STFC4	14.63	12
	3/4"	3/4" - 14	brass	2000	STFC6	23.54	12
	1"	1" - 11 1/2	brass	1000	STFC8	35.51	1
	1-1/4"	1-1/4" - 11 1/2	brass	800	STFC10	99.12	1
	1-1/2"	1-1/2" - 11 1/2	brass	600	STFC12	135.85	1
	2"	2" - 11 1/2	brass	400	STFC16	187.15	1
	1/4"	1/4" - 18	303 stainless	6700	STFC2SS	\$47.30	5
	3/8"	3/8" - 18	303 stainless	5500	STFC3SS	67.00	5
	1/2"	1/2" - 14	303 stainless	3000	STFC4SS	78.00	5
	3/4"	3/4" - 14	303 stainless	3000	STFC6SS	135.65	5
	1"	1" - 11 1/2	303 stainless	1700	STFC8SS	185.00	5

Male Couplers	Body Size	NPT Thread Size	Material	Operating PSI	Part #	Price/E	Pkg Qty
	1/4"	1/4" - 18	brass	4500	STMC2	\$8.49	12
	3/8"	3/8" - 18	brass	2700	STMC3	9.68	12
	1/2"	1/2" - 14	brass	2500	STMC4	14.47	12
	3/4"	3/4" - 14	brass	2000	STMC6	23.37	12
	1"	1" - 11 1/2	brass	1000	STMC8	39.24	1
	1/4"	1/4" - 18	303 stainless	6700	STMC2SS	\$49.00	5
	3/8"	3/8" - 18	303 stainless	5500	STMC3SS	61.45	5
	1/2"	1/2" - 14	303 stainless	3000	STMC4SS	84.65	5
	3/4"	3/4" - 14	303 stainless	3000	STMC6SS	155.50	5
	1"	1" - 11 1/2	303 stainless	1700	STMC8SS	260.50	5

Standard Hose Barbs	Body Size	Hose I.D.	Material	Operating PSI *	Part #	Price/E	Pkg Qty
	1/4"	1/4"	brass	5200	2ES2-B	\$9.85	100
	3/8"	3/8"	brass	2800	3ES3-B	12.14	50
	1/2"	1/2"	brass	2200	4ES4-B	19.48	25
	3/4"	3/4"	brass	1700	6ES6-B	29.44	20
	1"	1"	brass	1700	8ES8-B	41.18	10



* Operating pressures for the standard hose barbs utilizing hose barb end connections may be dramatically reduced to that of the hose rating and/or hose and end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon Valve and Coupling cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

Optional Pkg./Box Quantity Shown