

Bradford™ Sanitary Fittings

Clamps

3 Segment Clamps - 13MHHM-3P





	Pressure			
Tube	Pressure			
1" - 1½ 2" 2½" 3" 4" 12"	600 PSI 550 PSI 450 PSI 350 PSI 300 PSI 75 PSI	2.122 2.654 3.185 3.717 4.820 12.740	13MHHM-3P100150 13MHHM-3P200 13MHHM-3P250 13MHHM-3P300 13MHHM-3P400 13MHHM-3P1200	\$28.60 32.15 38.50 44.95 54.60 656.30

^{*} Wing nut tightened to 25 in. lbs. torque

Spring Loaded Nut






Dimensions		Throad	Dout #	Dries / Fook	
	Α	В	Thread	Part #	Price / Each
	1.73	.875	5/16 - 18	13SLN	\$91.15

- · Lines using PTFE gaskets subject to large temperature swings can benefit from the spring loaded nut. As the PTFE is compressed through the cycling of the lines, the spring load will keep the connection from leaking.
- If the lines suffer from vibration and bolted clamps are not an option, refitting single pin clamps with this nut will keep the connections from leaking for a longer time than the standard wing nuts.
- If you transport material in tanks via truck, the vibrations can loosen the standard single pin clamps. Spring loaded nuts can add a level of insurance to the shipment.
- Tighten to 50 in. lbs. as noted on the nut.

Bolted Clamps - 13MHP





Tube OD	Service Pressure Rating @ 70°F *	Service Pressure Rating @ 250°F *	Dimension A	304 Stainles Part #	s Steel Price / Each
1/2" - 3/4" 1" - 11/2" 2" 21/2" 3" 4" 6" 8" 10" 12"	1500 PSI 1500 PSI 1000 PSI 1000 PSI 1000 PSI 800 PSI 300 PSI 250 PSI 200 PSI	1200 PSI 1200 PSI 800 PSI 800 PSI 800 PSI 600 PSI 200 PSI 150 PSI 125 PSI 100 PSI	1.062 2.046 2.578 3.110 3.640 4.744 6.632 8.638 10.740 12.740	13MHP75 13MHP100-150 13MHP200 13MHP250 13MHP300 13MHP400 13MHP600 13MHP800 13MHP1000	\$33.35 26.25 31.75 34.85 39.45 50.45 91.75 285.60 902.10 1017.35

^{*} Bronze nuts tightened to 20 ft. lbs. torque

Toggle Clamps - 13MHLA



Tube	Service	Dimension	304 Stainless Steel	
OD	Pressure Rating @ 70°F *	A	Part #	Price / Each
1" - 1½"	150 PSI	2.122	13MHLA100-150	\$39.30
2"	150 PSI	2.654	13MHLA200	40.20
21/2"	150 PSI	3.185	13MHLA250	45.80
3"	150 PSI	3.717	13MHLA300	58.65
4"	100 PSI	4.820	13MHLA400	64.30

^{*} Screw tightened to maximum

DPL108 334