



## Fire Hose Fittings



### Constant Flow Thermoplastic Fog Nozzles

- Factory Mutual approved
- Red polycarbonate with bumper, black plastic and steel stem
- Adjusts from straight stream to fog
- 1" and 1½" are ULC listed

- For use up to **100 PSI** (*water only*)
- Provides consistent volume at any spray angle
- Replacement gaskets available below



2½" provided with handles



1" through 2"

Size	Thread	90° Spray GPM@ 100 PSI	Part #	Price / Each
¾"	GHT	8	<b>CFB75GHT</b>	<b>\$30.80</b>
1"	SIPT (NPSH)	22	<b>CFB100S</b>	<b>30.15</b>
1½"	SIPT (NPSH)	75	<b>CFB150S</b> <sup>1</sup>	<b>26.40</b>
1½"	SIPT (NPSH)	150	<b>HGCFB150S</b> <sup>2</sup>	<b>83.75</b>
2"	SIPT (NPSH)	75	<b>CFB2015S</b> <sup>1</sup>	<b>60.15</b>
2"	SIPT (NPSH)	150	<b>CFB200S</b> <sup>2</sup>	<b>84.40</b>
1"	NST (NH)	22	<b>CFB100NST</b>	<b>\$30.15</b>
1½"	NST (NH)	75	<b>CFB150NST</b> <sup>1</sup>	<b>26.40</b>
1½"	NST (NH)	150	<b>HGCFB150NST</b> <sup>2</sup>	<b>83.75</b>
2½"	NST (NH)	150	<b>CFB250NST</b> <sup>3</sup>	<b>171.15</b>
2½"	NST (NH)	215	<b>HGCFB250NST</b> <sup>2,3</sup>	<b>185.05</b>

<sup>1</sup> standard flow

<sup>2</sup> high flow

<sup>3</sup> provided with handles

### Blue Thermoplastic Refinery Fog Nozzles

- Bumper and black plastic and steel stems
- Glass-filled
- Provides consistent volume at any spray angle
- Adjusts from straight stream to fog
- Resistant to petrochemicals
- Factory Mutual approved
- For use up to **100 PSI** (*water only*)
- Replacement gaskets available below



Size	Thread	GPM @ 100 PSI	Part #	Price / E
1½"	SIPT	75	<b>RNB150S</b>	<b>\$31.55</b>
1½"	NST (NH)	75	<b>RNB150NST</b>	<b>31.55</b>

### Gaskets

- For use in Constant Flow and Refinery Fog Nozzles
- *All dimensions are nominal*



Size	Thread Type	Dimensions			Part #	Price/ E
		I.D.	O.D.	THK.		
1"	SIPT (NPSH)	.900"	1.270"	.125"	<b>CFG100S</b>	<b>\$2.60</b>
1½"	SIPT (NPSH)	1.510"	1.878"	.125"	<b>CFG150S</b>	<b>2.65</b>
2"	SIPT (NPSH)	1.680"	2.340"	.156"	<b>CFG200S</b>	<b>2.80</b>
1"	NST (NH)	.900"	1.270"	.125"	<b>CFG100NST</b>	<b>2.60</b>
1½"	NST (NH)	1.510"	1.906"	.125"	<b>CFG150NST</b>	<b>2.65</b>
2½"	NST (NH)	2.250"	3.000"	.187"	<b>CFG250NST</b>	<b>2.95</b>