

Fire Hose Fittings

U.S. Coast Guard Approved AFFF/Water Fog Nozzles

Nozzles designed for maximum efficiency with AFFF (Aqueous Film Forming Foams) or water on shipboard, offshore rigs and industrial applications.





Corrosion resistant brass construction

- Zytel® (nylon) horseshoe handle
- Flush without shutting down
- Constant gallonage in all fog and straight stream pattern
- Rubber-like bumper and handle for added protection
- Double row of molded teeth for excellent fog pattern
- Combination fog and straight stream
- Operating pressure up to 100 PSI (water and AFFF only)

Size	Thread	Description	Fog Flow @100 PSI	Orifice	Length	Weight	Approval #	Part #	Price / E
	NST(NH) NST(NH)	nozzle nozzle w/pistol grip	95 GPM 95 GPM	5/8" 15/16"	10¼" 11½"	9 lbs. 14.5 lbs.	162.027/13/0 162.027/11/0	CGSN150F CGSN151F	\$1628.00 1769.60

U.S. Coast Guard Approved Fog Nozzles

- Designed to U.S. Coast Guard specification for fighting fires with drafted water
- Required equipment for all commercial vessels under U.S. registry
- Corrosion resistant brass construction
- · Combination fog and straight stream for shipboard fire fighting
- Operating pressure up to 100 PSI (water only)

Size	Thread	Fog Flow @100 PSI	Approval #	Part #	Price / E
1½"	NST(NH)	55 GPM	162.027/9/0	CGN150NST	\$1572.20
2½"	NST(NH)	108 GPM	162.027/10/0	CGN250NST	1820.10

Applicators are available on special order. Consult the factory for pricing and availability.





Part #	Price / E
CGN150-TIP	\$347.80
CGN250-TIP	410.00





U/L Play Pipe with Tip

A component often required in hydrant houses by Insurance Underwriters.

- Swivel handle, red marlin trim
- For use up to 100 PSI (water only)
- Underwriters listed and Factory Mutual approved



Size	Female inlet	Male outlet	Orifice	Part #	Price / Each
2½"	NH (NST)	ULT *	1-1/8"	UPP250F	\$718.35

* ULT thread 2-3/16" ODM x 12 TPI





Tip for U/L Play Pipe

- Satin finish brass
- For use up to 100 PSI (water only)
- U/L listed and FM approved



Thread	Orifice	Part #	Price / Each
ULT *	1-1/8"	UPPT	\$154.50

* ULT thread 2-3/16" ODM x 12 TPI

416 DPL108







