



## Fire Hose Fittings

### Omega™ Monitor



- Brass construction
- Cast-in turning vanes for a more efficient flow
- 360° horizontal and 150° vertical travel
- Full 3" waterway
- Friction loss: 10 PSI at 800 GPM (.7 bar at 3030 LPM)
- Other configurations available

Size	Inlet Configuration	Outlet	Waterway	Flow	Weight	Part #	Price / E
17" x 11½"	3" flange	2½" male NST	3"	1250 GPM	72 lbs.	<b>AK3526-300FL</b>	<b>\$4450.95</b>



### Steel FirePro™ Monitor



- Seamless 2½" monitor - rated at 750 GPM
- Carbon steel construction
- Stainless steel discharge tip and ball bearings
- 360° horizontal and 140° vertical travel
- Red epoxy finish standard
- 150# ASA raised face 4" flange
- FM approved

Size	Inlet Configuration	Outlet	Waterway	Flow	Weight	Part #	Price / E
22" x 13"	4" flange	2½" male NST	2½"	750 GPM	50 lbs.	<b>FP475S</b>	<b>\$2664.25</b>

### Monitor Nozzle

Aquastream™ Master Stream, a fixed gallonage master stream designed for heavy-duty use on fixed monitors. Factory set at 500 GPM (1900 LPM) - can be changed in the field to 300 or 700 GPM (1140 or 2660 LPM). Operating pressure: **100 PSI** (*water only*)



- Brass construction
- Fixed teeth
- Swivel nut

Size	Thread	Length	Weight	Part #	Price / E
2½"	NST	7"	14.5 lbs.	<b>AK4450NST</b>	<b>\$1380.60</b>

Fire Hose Fittings