

Spiral Guard™ Flame Retardant Hose and Cable Protection

Provides heavy duty hose, cable or wire protection. Used in mining, quarrying, forestry, offshore industries and most hydraulic hose applications.

- Crush and high abrasion resistance
- Chemical and UV ray resistant
- Self-lubricating to reduce hose wear
- Easy to install on-site
- Smooth radius on all edges
- Can be used on single or multiple hose bundles



Flame Retardant Product

- Approved by MSHA 1C-231/1
- Flame retardant and self extinguishing
- Temperature range: **-148°F to 212°F, (-100°C to 100°C)**

Spiral Guard I.D.	Coil Length	O.D. Range (inches)	Flame Retardant Part #	Price/Coil
1/2"	66'	1/2" to 5/8"	FRSGX16	\$148.95
5/8"	66'	5/8" to 7/8"	FRSGX20	200.55
3/4"	66'	7/8" to 1-1/16"	FRSGX25	263.50
15/16"	66'	1-1/16" to 1-1/4"	FRSGX32	481.15
1-1/4"	66'	1-1/4" to 1-5/8"	FRSGX40	601.40
1-1/2"	66'	1-5/8" to 2-1/8"	FRSGX50	862.60
1-15/16"	66'	2" to 2-1/2"	FRSGX63	1092.00
2-3/8"	66'	2-1/2" to 3-1/4"	FRSGX75	1365.40
2-5/8"	66'	3" to 6"	FRSGX90	1555.60
3-3/16"	33'	6" plus	FRSGX110	1050.70

Standard Product

- **Not** flame retardant
- Temperature range: **-58°F to 194°F, (-50°C to 90°C)**

Spiral Guard I.D.	Coil Length	O.D. Range (inches)	Standard Product Part #	Price/Coil
1/2"	66'	1/2" to 5/8"	NFSGX16	\$74.50
5/8"	66'	5/8" to 7/8"	NFSGX20	106.00
3/4"	66'	7/8" to 1-1/16"	NFSGX25	144.35
15/16"	66'	1-1/16" to 1-1/4"	NFSGX32	209.10
1-1/4"	66'	1-1/4" to 1-5/8"	NFSGX40	309.35
1-1/2"	66'	1-5/8" to 2-1/8"	NFSGX50	401.00
1-15/16"	66'	2" to 2-1/2"	NFSGX63	567.00
2-3/8"	66'	2-1/2" to 3-1/4"	NFSGX75	788.70
2-5/8"	66'	3" to 6"	NFSGX90	1016.65
3-3/16"	33'	6" plus	NFSGX110	619.75

- Spiral guard I.D. is equal to the guard at rest
- Sold in coil lengths only

Fire Jackets for Hose

Used to protect hose and hose assemblies, tubing, piping, wiring and cables from high temperatures or molten splash. Helps maintain line temperature and reduce environmental overheating and overcooling.

- Resistant to hydraulic fluids and lubricating oil
- Color is iron oxide red
- Supplied in 50' lengths, (not continuous)
- Temperature range: **-65°F to 500°F (-54°C to 260°C)**
- Sleeving slides easily over hose and expands to go over fittings.
- Compounded silicone rubber coating over fiberglass
- Completely non-asbestos

Nominal I.D.	Part #	Price / Each
1/4"	0610-4	\$223.05
3/8"	1010-6	236.30
1/2"	1310-8	276.15
5/8"	1610-10	318.60
3/4"	1910-12	358.45
7/8"	2210-14	424.80
1"	2510-16	477.90
1-1/4"	3210-20	549.60
1-1/2"	3810-24	613.35
1-3/4"	4510-28	740.75
2"	5110-32	836.35
2½"	6410-40	1224.50
3"	7610-48	1840.90
4"	10210-64	2127.25

