




Single Clapper Siamese Connections

21-201 / 21-202



21-201

Y Type 'short body' - Single Clapper Siamese
Underwriters Listed. FM approved, ULC




Size	Dimensions (inches)		
	A	B	C
4 x 2½ x 2½	5-1/8	9	6-1/16



21-202

90° Single Clapper Siamese
Underwriters Listed



Size	Dimensions (inches)	
	A	B
4 x 2½ x 2½	6-7/8	9-7/8

Single swing clapper with (2) pin lug swivel inlets. Provides the required 500 gpm minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.) The swing clapper design provides unobstructed waterway. Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

- Cast brass finish
- U/L listed and FM approved
- Branding: **Auto-Sprk**
- For use up to **250 PSI**

- P polished
- C polished chrome plated

Back Outlet - (straight)

Outlet Female NPT	(2) Inlets Female NH (NST)	Dixon Part #	Powhatan Part #
4"	2½" NH	SCS4025F	21-201-01976
4"	2½" NH	SCS4025F-C	21-201-02004
4"	2½" NYFD	SCS4025NYFD	21-201-01992

Bottom Outlet - (90°)

Outlet Female NPT	(2) Inlets Female	Dixon Part #	Powhatan Part #
4"	2½" NH	90SCS4025F	21-202-00054
4"	2½" NH	90SCS4025F-SP	21-202-00066
4"	2½" NYFD	90SCS4025NYFD	21-202-00082