

300# Single Jacket All-Polyester Fire Hose - White

Ideal for open end discharge applications.
Not intended for fire fighting service.

- Outer construction: single jacket, all polyester
- Tube construction: black, extruded synthetic rubber
- Proof Pressure: **300 PSI**
- Service Test Pressure: **150 PSI**
- Working Pressure: **135 PSI**

- Uncoupled

Hose Size	Bowl Size	Length	Dixon Part #
1½"	1-13/16"	50'	A315-50UC
1½"	1-13/16"	100'	A315-100UC
2½"	2-7/8"	50'	A325-50UC
2½"	2-7/8"	100'	A325-100UC



- Coupled with female and male expansion ring couplings

Thread NH (NST)	Coupling Type	Length	Dixon Part #
1½"	Rocker lug, <i>aluminum</i>	50'	A315-50RAF
1½"	Rocker lug, <i>aluminum</i>	100'	A315100RAF
1½"	Rocker lug, <i>brass</i>	50'	A315-50RBF
1½"	Rocker lug, <i>brass</i>	100'	A315100RBF
2½"	Rocker lug, <i>aluminum</i>	50'	A325-50RAF
2½"	Rocker lug, <i>aluminum</i>	100'	A325100RAF
2½"	Rocker lug, <i>brass</i>	50'	A325-50RBF
2½"	Rocker lug, <i>brass</i>	100'	A325100RBF



- Coupled with female and male expansion ring couplings

Thread NPSH	Coupling Type	Length	Dixon Part #
1½"	Rocker lug, <i>aluminum</i>	50'	A315-50RAS
1½"	Rocker lug, <i>aluminum</i>	100'	A315100RAS
2½"	Rocker lug, <i>aluminum</i>	50'	A325-50RAS
2½"	Rocker lug, <i>aluminum</i>	100'	A325100RAS

- Other lengths, threads and couplings are also available. *Consult the factory for pricing and availability.*

- * Working pressures can be achieved using appropriate expansion ring couplings.

Under no circumstance should the hose be used beyond the working pressure of the fittings to which it is coupled.
 Assembled hose should be hydrostatically proof tested before use, and thereafter in accordance with NFPA 1962.