

## Forestry Fire Hose - Non-Weeping

- Outer construction: single jacket, synthetic
- Tube construction: thermoplastic
- Impregnation color: yellow
- Proof Pressure: **600 PSI**
- Service Test Pressure: **300 PSI**
- Working Pressure: **270 PSI**

- Coupled with female and male expansion ring couplings

Thread NH (NST)	Coupling Type	Length	<i>Dixon Part #</i>
1½"	Rocker lug, <i>aluminum</i>	50'	<b>NF615Y50RAF</b>
1½"	Rocker lug, <i>aluminum</i>	100'	<b>NF615Y100RAF</b>



- Coupled with female and male expansion ring couplings

Thread NPSH	Coupling Type	Length	<i>Dixon Part #</i>
1"	Rocker lug, <i>aluminum</i>	50'	<b>NF610Y50RAS</b>
1"	Rocker lug, <i>aluminum</i>	100'	<b>NF610Y100RAS</b>

- Other lengths, threads and couplings are also available.  
*Consult the factory for pricing and availability.*

## Forestry Mop Up Hose

Forest fire applications include mop-up, low volume hand lines, filling pump cans, supplying sprinklers and remote fire line protection. 50' coil diameter is 9"

- Outer construction: single jacket, synthetic
- Tube construction: thermoplastic
- Impregnation color: yellow
- Proof Pressure: **300 PSI**
- Service Test Pressure: **150 PSI**
- Working Pressure: **135 PSI**

- Coupled with female and male brass ferrule type garden hose couplings

Thread GHT	Coupling Type	Length	<i>Dixon Part #</i>
¾"	---	50'	<b>NF307Y50GHT</b>



- Other lengths, threads and couplings are also available.  
*Consult the factory for pricing and availability.*