

## 500# Nitrile Covered Fire Hose - Light Duty Red

- Outer construction: thin, ribbed nitrile
- Tube construction: nitrile
- Proof Pressure: **500 PSI**
- Service Test Pressure: **250 PSI**
- Working Pressure: **225 PSI**

- Uncoupled

Hose Size	Bowl Size	Length	Dixon Part #
1½"	1¾"	50'	<b>H515R50UC</b>
1½"	1¾"	100'	<b>H515R100UC</b>
2½"	2¾"	50'	<b>H525R50UC</b>



- Coupled with female and male expansion ring couplings

Thread NH (NST)	Coupling Type	Length	Dixon Part #
1½"	Rocker lug, <i>aluminum</i>	50'	<b>H515R50RAF</b>
1½"	Rocker lug, <i>aluminum</i>	100'	<b>H515R100RAF</b>
1½"	Rocker lug, <i>brass</i>	50'	<b>H515R50RBF</b>
1½"	Rocker lug, <i>brass</i>	100'	<b>H515R100RBF</b>
2½"	Rocker lug, <i>aluminum</i>	50'	<b>H525R50RAF</b>
2½"	Rocker lug, <i>aluminum</i>	100'	<b>H525R100RAF</b>
2½"	Rocker lug, <i>brass</i>	50'	<b>H525R50RBF</b>



- Coupled with female and male expansion ring couplings

Thread NPSH	Coupling Type	Length	Dixon Part #
1½"	Rocker lug, <i>aluminum</i>	50'	<b>H515R50RAS</b>
1½"	Rocker lug, <i>aluminum</i>	100'	<b>H515R100RAS</b>
2½"	Rocker lug, <i>aluminum</i>	50'	<b>H525R50RAS</b>

- Other lengths, threads and couplings are also available. *Consult the factory for pricing and availability.*
- Colors available; yellow, red blue and black.

\* Working pressures can be achieved using appropriate expansion ring couplings.

***Under no circumstance should the hose be used beyond the working pressure of the fittings to which it is coupled.***  
Assembled hose should be hydrostatically proof tested before use, and thereafter in accordance with NFPA 1962.