

Nitrile Covered Fire Hose - Heavy Duty Yellow

- Outer construction: thick ribbed nitrile
- Tube construction: nitrile

Proof Pressure:

1" - 3" - 600 PSI
4" - 450 PSI
5" - 400 PSI
6" - 300 PSI

Service Test Pressure:

1" - 3" - 300 PSI
4" - 225 PSI
5" - 200 PSI
6" - 150 PSI

Working Pressure:

1" - 3" - **270 PSI**
4" - **200 PSI**
5" - **180 PSI**
6" - **135 PSI**



- Uncoupled

Hose Size	Bowl Size	Length	Dixon Part #
1"	1-1/4"	50'	H610Y50UC
1"	1-1/4"	100'	H610Y100UC
1½"	1-13/16"	50'	H615Y50UC
1½"	1-13/16"	100'	H615Y100UC
2"	2-3/16"	50'	H620Y50UC
2"	2-3/16"	100'	H620Y100UC
2½"	2-7/8"	50'	H625Y50UC
2½"	2-7/8"	100'	H625Y100UC
3"	3-13/32"	50'	H630Y50UC
3"	3-13/32"	100'	H630Y100UC
4"	4-5/16"	50'	H440Y50UC
4"	4-5/16"	100'	H440Y100UC
6"	6-5/16"	50'	H360Y50UC
6"	6-5/16"	100'	H360Y100UC

- Coupled with female and male expansion ring couplings

Thread NH (NST)	Coupling Type	Length	Dixon Part #
1"	Rocker lug, <i>aluminum</i>	50'	H610Y50RAF
1"	Rocker lug, <i>brass</i>	50'	H610Y50RBF
1½"	Rocker lug, <i>aluminum</i>	50'	H615Y50RAF
1½"	Rocker lug, <i>aluminum</i>	100'	H615Y100RAF
1½"	Rocker lug, <i>brass</i>	50'	H615Y50RBF
1½"	Rocker lug, <i>brass</i>	100'	H615Y100RBF
2½"	Rocker lug, <i>aluminum</i>	50'	H625Y50RAF
2½"	Rocker lug, <i>aluminum</i>	100'	H625Y100RAF
2½"	Rocker lug, <i>brass</i>	50'	H625Y50RBF
2½"	Rocker lug, <i>brass</i>	100'	H625Y100RBF
3"	Rocker lug, <i>aluminum</i>	50'	H630Y50RAF
3"	Rocker lug, <i>aluminum</i>	100'	H630Y100RAF

- Coupled with female and male expansion ring couplings

Thread NPSH	Coupling Type	Length	Dixon Part #
1"	Rocker lug, <i>aluminum</i>	50'	H610Y50RAS
1"	Rocker lug, <i>brass</i>	50'	H610Y50RBS
2"	Rocker lug, <i>brass</i>	50'	H620Y50RBS
2"	Rocker lug, <i>brass</i>	100'	H620Y100RBS

- Coupled with female and male segmented collar style couplings

Thread NPSH	Coupling Type	Length	Dixon Part #
4"	Storz	50'	H440Y50SZ
4"	Storz	100'	H440Y100SZ
5"	Storz	50'	H450Y50SZ
5"	Storz	100'	H450Y100SZ

- Other lengths, threads and couplings are also available. *Consult the factory for pricing and availability.*
- Colors available; yellow, red blue and black.

* Working pressures can be achieved using appropriate expansion ring couplings.

Under no circumstance should the hose be used beyond the working pressure of the fittings to which it is coupled.

Assembled hose should be hydrostatically proof tested before use, and thereafter in accordance with NFPA 1962.