


Non-collapsible Fire and Utility Hose - Red

- The red outer cover is designed to withstand abrasion
- Working Pressure: **150 PSI**
- Coupled with female and male expansion ring couplings

Thread NH (NST)	Coupling Type	Length	Dixon Part #
1½"	Rocker lug, <i>brass</i>	50'	15B15-50RBF
1½"	Rocker lug, <i>brass</i>	100'	15B15-100RBF



- Other lengths, threads and couplings are also available.
Consult the factory for pricing and availability.

Boostlite Lightweight Non-collapsible Reel Hose - Yellow

- Minimum bend radius of 9" makes hose kink resistant
- Superior lining adhesion provides a smoother waterway resulting in lower friction loss
- Outer construction: single jacket, all synthetic
helically reinforced
- Tube construction: clear polyurethane
- Impregnation color: yellow
- Proof Pressure: **800 PSI**
- Service Test Pressure: **400 PSI**
- Working Pressure: **360 PSI**
- Coupled with female and male expansion ring couplings

Thread	Coupling Type	Length	Dixon Part #
1" NPSH	Rocker lug, <i>aluminum</i>	100'	BL810Y100RAS
1" NH (NST)	Rocker lug, <i>aluminum</i>	100'	BL810Y100RAF



*shown on reel
(reel not included)*

- ¾" and 1" NST (NH) threads are the same size.
Also known as Chemical Hose Thread (CHT) or Booster Hose Thread

Non-collapsible Chemical Booster Hose - Red

- The vertical braid construction and red ozone resistant outer cover are designed to withstand weathering and abrasion associated with severe service
- Working Pressure: **800 PSI**
- Coupled with female and male hole type couplings

Thread NH (NST)	Coupling Type	Length	Dixon Part #
¾"	Hole type, <i>chromed brass</i>	50'	80B07-50HCF
¾"	Hole type, <i>chromed brass</i>	100'	80B07-100HCF
1"	Hole type, <i>chromed brass</i>	50'	80B10-50HCF
1"	Hole type, <i>chromed brass</i>	100'	80B10-100HCF



- Other lengths, threads and couplings are also available.
Consult the factory for pricing and availability.
- ¾" and 1" NST (NH) threads are the same size.
Also known as Chemical Hose Thread (CHT) or Booster Hose Thread