

Aluminum Barrel Strainers

- Lightweight
- Brite aluminum finish
- Full flow design
- Rocker lugs
- Tie off hook for drafting placement


NH (NST) Thread	Dixon Part #
2½"	BBS250F
3"	BBS300F
4"	BBS400F
4½"	BBS450F
5"	BBS500F
6"	BBS600F



Hardcoated aluminum, red anodized aluminum or brass is also available.
Consult the factory for price and availability.
Not all sizes are stocked.

Aluminum Floating Strainers

NH (NST) Thread	Dixon Part #
2½"	AFS250F
3"	AFS300F
4"	AFS400F
4½"	AFS450F
5"	AFS500F
6"	AFS600F
Storz	Dixon Part #
5"	AFS500SZ



Other versions with Storz or Cam and Groove connections are available.
Consult the factory for price and availability.

Round Hole Strainer

- Zinc plated steel

NH (NST) Thread	Dixon Part #
2½"	RHS3075



Chrome plated is also available. Consult the factory for price and availability.

Strainer with Spring-Loaded Check Valve

- 1½" - 2" rated to **400 PSI** WOG;
3" - 4" rated to **175 PSI** WOG
- Cracking pressure: **.50 PSI**
- Brass with NBR seat
- Stainless steel strainer
- Soft seat for bubble tight shutoff, spring loaded for fast seating action.
- Flow profile designed to minimize head loss
- Temperature range **10°F to 210°F** (-10°C to 100°C)

Size	Dixon Part #
1½"	BVFS20
2"	BVFS25
3"	BVFS35
4"	BVFS40

