



A

Ordering Information

Filter / Strainer

Manufacturer (1)	Type (2)	End Configuration (3-4)	Clamp Type (5)	Length (6)	(7)	Stainless Grade (8)	Size (9-11)
B Bradford™	S strainer	C clamp	S single pin	1 short	-	R 316L	100 1"
	F filter	B butt-weld	Q squeeze clamp	2 long			150 1½"
		F female I-line					200 2"
		M male I-line					250 2½"
		T threaded bevel					300 3"
		P plain bevel					
		Q Q-line					
		J John Perry					
		H John Perry threaded					
		E extended butt-weld					

Ordering Example:

1 2 3 4 5 6 7 8 9 10 11
 B S C C Q 2 - R 2 0 0

Description:

316L 2" long strainer with clamp ends and squeeze clamp

Note:

- When ordering please list part number along with description. See pages 153-157 for more information.
- Squeeze clamp is standard on all units. Long units not available in all sizes

Gauges

Dial Size (1-2)	Type of Gauge (3-6)	Material (7)	Case Fill Type (8)	Connection Size (9-10)	Mount (11)	Pressure Range (12-14)
20 2"	1032 sanitary	S stainless	D dry	75 ¾"	L lower	15
25 2½"	1036 in-line		L glycerin	15 1½"	B back	30
30 3"	1037 instrument tee			20 2"		60
35 3½"	2032 digital					100
45 4½"						160
						200
						300
						400
						600

Ordering Example:

1 2 3 4 5 6 7 8 9 10 11 12 13 14
 3 5 1 0 3 2 S L 1 5 L 1 0 0

Description:

1032 gauge with a 3½" dial glycerin filled with an 1½" lower mount 100 PSI

Note:

- When ordering please list part number along with description. See pages 160-165 for more information.
- Not all styles of gauges are available in all sizes.