# **Legris Accessories**

## Nylon/Nickel-Plated Brass Push-In Fittings

Materials: Nickel-plated brass construction. Black body is glass-filled nylon; Buna-N O-ring seal; polypropylene release button. Silicone free.

Positive Seal: sealing and holding is accomplished instantaneously

Reusable: connect and disconnect numerous times Full Flow: fitting seals on outside diameter of tubing Working Pressure: fittings rated to 290 PSI at ambient temperature



## Male Swivel Run Tees (Tube to Male NPT)

``		/	
Tube	Male	Plated Brass	
O.D.	NPT	Part #	
1/4"	1/8"	3103 56 11	

### Male Swivel Elbows (Tube to Male NPT)

Tube	Male	Plated Brass	
O.D.	NPT	Part #	
1/4"	1/8"	3109 56 11	
1/4"	1/4"	3109 56 14	


#### 45° Male Elbows (Tubo to Mole NDT)

(Tube to Male NPT)			
Tube	Male	Plated Brass	
O.D.	NPT	Part #	
1/4"	1/8"	3113 56 11	
1/4"	1/4"	3113 56 14	

Working Temperature: -4°F to 175°F

SAFETY Maximum circuit pressure depends equally on the type and diameter of the tube used. Pre-applied thread sealant on all male pipe threads Compatible Tubing: semi-rigid nylon, polyurethane and

polyethylene tube Vacuum Capability: vacuum of 28" Hg (99% vacuum)



Quick Connect and Disconnect: Simply push tubing in. To remove, press the release ring towards the fitting and pull tubing out. No tools required.

### Male Connectors (Tube to Male NPT)

Tube	Male	Plated Brass	
O.D.	NPT	Part #	
1/4"	1/8"	3175 56 11	
1/4"	1/4"	3175 56 14	

**Male Connectors** 

(Tube to Male BSPT)

Tube	Male	Plated Brass
O.D.	BSPT	Part #
1/4"	1/8"	3175 56 10
1/4"	1/4"	3175 56 13



0

Mini Ball Valves		
Tube O.D.	Desc.	Par
1/4" 1/4"	with vent w/o vent	

#### w/o vent 7910 56 00

Part #

7913 56 00

Lockable Slide Valves (Double Female)


(				
Tube O.D.	Female NPT	Part #		
1/8" 1/4"	1/8" 1/4"	0662 06 11 0662 08 14		

Valves

Materials: Nylon body. Nickel-plated brass ball Suitable fluid: compressed air Maximum pressure: 145 PSI Vacuum capability: vacuum of 28" Hg (99% of vacuum) Working temperature: -4°F to 175°F

The lockable slide valves can accommodate standard lock shank sizes up to 0.145".

## Lock-Out Tag-Out Fittings



#### Tubing (100 ft. rolls) Tube Polyurethane Color O.D. Part # 1094U5601 black

red

blue

WebSales@GoodyearRubberProducts.com

Call Toll Free: 1-866-711-467

1094U5603

1094U5604

1/4" 1/4" 1/4"

Dixon Sanitary 2008 Catalog

Male

thread

1/8"NPT

1/4"BSPP

GOODYEAR

132

We Ship

World Wide

Part #

0121 11 10

0121 14 13