

Vapor Hose Couplers

- For use with vapor hose
- Cast aluminum body
- Buna gasket
- **VR4030CS-AL** has Viton® poppet seal

Part #	Description
VRC3000AL	3" coupler with probe x 3" hose shank
400-CVR-AL	4" coupler with probe x 4" hose shank
4030-CVR-AL	4" coupler with probe x 3" hose shank
VR4030CS-AL	4" coupler with poppet and probe x 3" hose shank
VR4030CS-NP	4" coupler no poppet and probe x 3" hose shank
4030-DAVR-AL	4" coupler with poppet and probe x 3" adapter
4030-DVR-AL	4" coupler with probe x 3" female NPT
400-DVR-AL	4" coupler with probe x 4" female NPT



VRC3000AL



VR4030CS-AL

Sequential Vapor Vents

Sequential vapor vents are used for venting tank vapors during the bottom loading and unloading of petroleum tankers. These pneumatically activated vapor vents can either be installed to open in a sequence or to open independently in either 16" or 20" tank manholes.

- Highest flow vapor recovery vents on the market
- Baylast seals resist chemical attack from fuel additives and alcohol
- Floating piston design ensures long life and resists poppet sticking
- Can be used for both sequential and non-sequential operation
- Quick and easy to rebuild with simple hand tools
- Tested vapor tight to 36 PSI, certification 49 CFR 178.345-5
- Sealed system eliminates common leak points and improves reliability
- VR6030SQ / VR6035SQ: effective February 2007 all standard gaskets will be Baylast
- Effective immediately the following vapor valves will be offered in Viton® gaskets for bio-diesel up to B100:
 - **VR6030SQV** - 16" sequential vent valve, Viton® gasket
 - **VR6030V** - 16" non-sequential vapor vent valve, Viton® gasket
 - **VR6035SQV** - 20" sequential vapor vent valve, Viton® gasket
 - **VR6030RKV1** - 16" repair kit, piston sub-assembly, poppet Viton® gasket
 - **VR6030RKV3** - 16" repair kit, poppet Viton® gasket
 - **VR6035RKV1** - 20" repair kit, piston sub-assembly, poppet Viton® gasket
 - **VR6035RKV3** - 20" repair kit, poppet Viton® gasket



VR6030SQ (16")



VR6035SQ (20")



40193AL

Part #	Description
VR6030SQ	For 16" manhole, mounting ring attachment
VR6035SQ	For 20" manhole, 3" TTMA flange attachment
40193AL	VR6035 adapter flange for Parker style vents


Replacement Part Kits

Part #	Description
VR6030RK1	VR6030SQ (16") complete rebuild kit
VR6030RK2	VR6030SQ (16") replacement piston assembly (<i>piston and lip seals</i>)
VR6030RK3	VR6030SQ (16") replacement vapor poppet gasket only
VR6035RK1	VR6035SQ (20") complete rebuild kit
VR6035RK2	VR6035SQ (20") replacement piston assembly (<i>piston and lip seals</i>)
VR6035RK3	VR6035SQ (20") replacement vapor poppet gasket only

Vent Hood

Designed specifically to fit with Nordic Posi-Vent only. The hood conveniently clamps to the 8-3/8" Posi-Vent outer flange of the mechanical compartment vent.

- Cast aluminum
- Comes with Buna gasket and steel ring clamp for flange mounting
- Machined base for tight gasket seal mounting



Part #
VRVH8380