


## Quick Release Couplings

Quick release couplings are specially designed for applications requiring a quick connection and/or disconnection of a pipe joint. A locking pin through the handle prevents accidental opening of the coupling. Ductile iron body with zinc plating and steel safety clip.




Interchangeable with:  
Victaulic's #78  
Grinnell's #7003



Part #	Nominal Size	Pipe O.D.	Max PSI	Max End Load lbs.	Coupling Dimensions			Approximate Weight Lbs.
					A	B	C	
<b>H315BU</b>	1½"	1.900"	<b>500</b>	850	4-3/4"	3-1/2"	1"	1.5
<b>H32BU</b>	2"	2.375"	<b>500</b>	1329	5-1/2"	3-3/4"	1-3/4"	2.5
<b>H325BU</b>	2½"	2.875"	<b>500</b>	2120	5-7/8"	4-3/4"	1-7/8"	4.0
<b>H33BU</b>	3"	3.500"	<b>500</b>	2886	7-1/4"	5-1/4"	1-3/4"	3.8
<b>H34BU</b>	4"	4.500"	<b>500</b>	4771	8-1/2"	6-1/2"	2"	6.0
<b>H36BU</b>	6"	6.625"	<b>500</b>	10341	10-5/8"	8-1/2"	2"	8.6

## Lightweight Flexible Couplings

Lightweight flexible couplings are designed for applications requiring moderate internal pressure or where weight is a factor. Applications include; general purpose, mining, irrigation, and compressed air where a deflection of 5% or less is required. Ductile iron body with rust inhibiting paint. **UL Listed and FM approved.**



Interchangeable with:  
Victaulic's #75  
Grinnell's #7000



Part #	Nominal Size	Pipe O.D.	Max PSI	Max End Load lbs.	Coupling Dimensions			Bolts		Approximate Weight Lbs.
					A	B	C	Qty.	Size	
<b>L215BU</b>	1½"	1.900"	<b>500</b>	1418	4-1/2"	2-7/8"	1-3/4"	2	3/8" x 1-7/8"	1.5
<b>L02BU</b>	2"	2.375"	<b>500</b>	2215	5-5/32"	3-11/32"	1-3/4"	2	3/8" x 1-7/8"	1.7
<b>L025BU</b>	2½"	2.875"	<b>300</b>	3246	5-25/32"	3-29/32"	1-3/4"	2	3/8" x 2"	2.2
<b>L03BU</b>	3"	3.500"	<b>300</b>	4811	6-35/64"	4-3/8"	1-51/64"	2	1/2" x 2-1/2"	2.8
<b>L04BU</b>	4"	4.500"	<b>300</b>	6362	8-3/64"	5-21/32"	1-15/16"	2	1/2" x 2-3/4"	3.7
<b>L05BU</b>	5"	5.563"	<b>300</b>	9722	9-1/2"	6-3/4"	2"	2	5/8" x 3-1/4"	5.7
<b>L06BU</b>	6"	6.625"	<b>300</b>	13789	10-53/64"	7-7/8"	2"	2	5/8" x 3-1/4"	7.4