

Horizontal Swing Check Valves



Female NPT x Female NPT

- Swing check valves are designed to prevent backflow in plumbing and liquid piping systems, while offering full flow performance with a minimum of turbulence or pressure loss.
- A positive seating disc allows flow only in one direction and a screw-in cap provides easy access for periodic cleaning.
- For horizontal or vertical use
- Rated to **200 PSI WOG**
- Brass body and disc
- Temperature range **-20° to 150°F**

Part #	Size
SWCV50	½"
SWCV75	¾"
SWCV100	1"
SWCV125	1¼"
SWCV150	1½"
SWCV200	2"
SWCV300	3"

In-Line Sight Glasses



3544CA

- Designed for dry bulk transfer applications.
- Available in combination of 3" and 4" coupler or adapter ends.
- Use sight glass kit - 6400SGK
- Includes:
 - Aluminum bodies
 - Buna seals
 - Acrylic sight glasses
 - Stainless steel hardware
 - Bronze cam arms (where applicable)

Part #	Description
3544CA	4" coupler x 4" adapter
3533CA	3" coupler x 3" adapter
3543CA	4" coupler x 3" adapter
3534CA	3" coupler x 4" adapter
3533AA	3" adapter x 3" adapter

Part #	Description
3544AA	4" adapter x 4" adapter
3534AA	3" adapter x 4" adapter
3544CC	4" coupler x 4" coupler
3533CC	3" coupler x 3" coupler
3543CC	4" coupler x 3" coupler