


# Adapter Nipples

These fittings are designed to provide minimum pressure drop and uniform strength. Maximum working pressure is **1000 PSI**.


## Short Hex Style - Series HN

Nominal Size	E to E	Carbon Steel Part #
2"	2-3/8"	<b>A712S</b>
2-1/2"	2-5/8"	<b>A7125S</b>
3"	2-7/8"	<b>A713S</b>
4"	3-1/2"	<b>A714S</b>



## Long Pipe Style - Series AN

Nominal Size	E to E	Carbon Steel Part #
2"	4"	<b>A712</b>
2-1/2"	4"	<b>A7125</b>
3"	4"	<b>A713</b>
4"	6"	<b>A714</b>
5"	6"	<b>A715</b>
6"	6"	<b>A716</b>



## Victaulic x Weld


Size	Aluminum Part #	Carbon Steel Part #	316 Stainless Steel Part #
2"	<b>AVN2000-200</b>	<b>VN2000-200</b>	<b>VNR2000-200</b>
2-1/2"	<b>AVN2500-200</b>	<b>VN2500-200</b>	<b>VNR2500-200</b>
3"	<b>AVN3000-200</b>	<b>VN3000-200</b>	<b>VNR3000-200</b>
4"	<b>AVN4000-200</b>	<b>VN4000-200</b>	<b>VNR4000-200</b>



# Quick Release Couplings

Quick Release couplings are specially designed for applications requiring a quick connection and/or disconnection of a pipe joint. A locking pin through the handle prevents accidental opening of the coupling. Ductile iron body with zinc plating and steel safety clip.

Interchangeable with:  
Victaulic's #78  
Grinnell's #7003



Nominal Size	Pipe O.D.	Max PSI	Max End Load Lbs.	Coupling Dimensions			Approx. Weight Lbs.	Part # w/EPDM gasket	Part # w/Buna-N gasket
				A	B	C			
1-1/2"	1.900"	<b>500</b>	850	4-3/4"	3-1/2"	1"	1.5	<b>H315</b>	<b>H315BU</b>
2"	2.375"	<b>500</b>	1329	5-1/2"	3-3/4"	1-3/4"	2.5	<b>H32</b>	<b>H32BU</b>
2-1/2"	2.875"	<b>500</b>	2120	5-7/8"	4-3/4"	1-7/8"	4.0	<b>H325</b>	<b>H325BU</b>
3"	3.500"	<b>500</b>	2886	7-1/4"	5-1/4"	1-3/4"	3.8	<b>H33</b>	<b>H33BU</b>
4"	4.500"	<b>500</b>	4771	8-1/2"	6-1/2"	2"	6.0	<b>H34</b>	<b>H34BU</b>
6"	6.625"	<b>500</b>	10341	10-5/8"	8-1/2"	2"	8.6	<b>H36</b>	<b>H36BU</b>

# NPT Threaded Pipe Fittings

Schedule 40 Pipe



Size	Overall Length	Carbon Steel Part #	304 Stainless Steel Part #	Aluminum Part #
1/4"	2"	<b>PN250</b>	<b>PNS250</b>	----
3/8"	2"	<b>PN375</b>	<b>PNS375</b>	----
1/2"	2"	<b>PN500</b>	<b>PNS500</b>	----
3/4"	2"	<b>PN750</b>	<b>PNS750</b>	----
1"	2"	<b>PN1000</b>	<b>PNS1000</b>	----
1-1/4"	2"	<b>PN1250</b>	<b>PNS1250</b>	----
1-1/2"	2"	<b>PN1500</b>	<b>PNS1500</b>	----
2"	2"	<b>PN2000</b>	<b>PNS2000</b>	----
2-1/2"	3"	<b>PN2500</b>	<b>PNS2500</b>	----
3"	3"	<b>PN3000</b>	<b>PNS3000</b>	<b>APN3000</b>
4"	4"	<b>PN4000</b>	<b>PNS4000</b>	<b>APN4000</b>

# King Combination Nipples



Hose nipples, made from tubular stock, to fit straight end hose. Threaded end, in all styles, has male NPT thread. Combination nipples are recommended for low-pressure discharge and suction service for compatible liquids. **Not for compressible products such as air or nitrogen on sizes 1 1/4" and above.** The working pressure of combination nipples will vary with the size and construction of the hose, the type and number of clamps used, clamp placement, proper installation of clamps, temperature and product being conveyed. In accordance with the RMA bulletin for oil suction and discharge hose, a coupled length of hose, in any size should be tested to 1 1/2 times the working pressure and held for fifteen minutes without leaking or coupling movement. Consult Dixon for recommendations specific to the application. **King Combination Nipples are not recommended for steam.**

