

Garlock Gasketing

Contents

Gasketing Products

Introduction	C-2
Quick Reference Selection Guide	C-3
Compressed Inorganic Fiber Gasketing	C-4
Style ST-706	C-5
Style IFG® 5500 and 5507	C-5
High Temp Compressed Graphite or Carbon Fiber Gasketing	C-6
Style G-9900	C-7
Styles 9800, 9850	C-7
BLUE-GARD® Compressed Gasketing	C-8
Styles 3000 to 3700	C-9
Styles 2900 / 2950 Gasketing	C-9
AGRI-GARD™ Style 2676	C-10
LEAK-GARD™ Style 3750	C-10
MULTI-SWELL™ Style 3760	C-10
GYLON® Gasketing	C-11
Styles 3500, 3504, 3510	C-13
Style 3530	C-13
Style 3535 Joint Sealant	C-13
Style 3540	C-14
Style 3545	C-14
Styles HP 3560, HP 3561	C-15
Style 3565 ENVELON®	C-15
Style 3522 Diaphragm Material	C-17
Welded GYLON®	C-17
STRESS SAVER® Gasketing	C-16
GRAPH-LOCK® Gasketing	C-18
Style 3128 HOCHDRUCK®	C-18
Styles 3120 to 3128	C-19
Premium Grade Rubber Gasketing	C-20
Styles 22, 7797, 7986, 8314, 9064, 9122, 9518, 9520, 9780	C-21
Reinforced Rubber Gasketing & Diaphragm....	C-22
Styles 19, 7992, 8798, 9200	C-22
Vegetable Fiber Gasketing	C-23
Styles 660, 670, 681	C-23



Engineering Data

Factors Affecting Gasket Performance	C-24
Gasket Selection	C-24
Chemical Resistance Chart	C-26
Sheet Sizes and Tolerances	C-39
"M" and "Y" Data	C-40
Gasket Constants	C-40
ASTM F104 Line Callouts	C-41
Bolting and Flange Information	C-42
Before Installation	C-43
Installation	C-43
Gasket Assembly Stress Recommendations ...	C-43
Torque and Stress Tables	C-44
Gasket Design Tips	C-48
Gasketing Terms	C-49
Test Procedures	C-54
Test Equipment	C-57
Application Data Form	C-58



AGRI-GARD™, LEAK-GARD™, and Multi-Swell™ are trademarks of Garlock Inc.

BLUE-GARD®, ENVELON®, GRAPH-LOCK®, GYLON®, IFG®, and STRESS SAVER® are registered trademarks of Garlock Inc.